

# Through Roof Fan Kits

High quality aluminium cowl construction with fan incorporated. 2 year warranty.

## Through Roof Fan Cowls with Flashing & HDPE Tube - Air Extraction

Classic	Tube (mm Ø)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Product Code
					(l/s)	(m³/hr)				
	250	Centrifugal	75	300	178	640	0.42	72	Standard	FAN2122
		Centrifugal (High Performance)	135	545	265	954	0.51	70	Standard	FAN2123
	150	Centrifugal	70	320	153	550	0.46	62	Standard	FAN0530
		Centrifugal (3-Speed)	70	320	153	550	0.46	62	Standard	FAN0967
		EC Axial	18	91	105	380	0.17	38	Standard	FAN1060 FAN0532

## Through Roof Fan Heavy Duty Cowls with Flashing & HDPE Tube - Air Extraction

Classic	Tube (mm Ø)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Product Code
					(l/s)	(m³/hr)				
	150	Centrifugal	70	320	153	550	0.46	62	Standard	FAN0740
		EC Axial	18	91	105	380	0.17	38	Standard	FAN0739

## Through Roof Fan Cowls with Flashing & HDPE Tube - Air Supply

Classic	Tube (mm Ø)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Product Code
					(l/s)	(m³/hr)				
	150	EC Axial	18	91	105	380	0.17	38	Standard	FAN0534

## Through Roof Fans with Flashing for Metal Based Roof - Air Extraction

Classic	Tube (mm Ø)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Product Code
					(l/s)	(m³/hr)				
	150	Centrifugal	70	320	153	550	0.46	62	Standard	FAN0535
	150	EC Axial	18	91	105	380	0.17	38	Standard	DCT0189


## Accessories

Model	Cowl	Filter Ring	Insect Mesh
FAN2122 FAN2123	DCT2241	DCT2254	DCT2253

# Through Roof Fan Kits

## Dimensions (mm)

Model	A	B	C
FAN0530 FAN0532 FAN0534 FAN0739 FAN0740 FAN0967 FAN1060	275	170	500



## Technical

Model	FAN2121 FAN2123	FAN0530 FAN0740	FAN0967	FAN0532 FAN0739	FAN0534	FAN1060
Supply	220-240V AC, 50Hz					
Max. Operating Temp	-25°C - 60°C		-25°C - 50°C		-20°C - 45°C	
IP Rating	IP44		IPX4		IP44	

