



# SmartBright All-in Floodlight

## BVP158 LED60/WW\_NW\_CW PSU 50W SWB GM

SmartBright All-in Floodlight, 5500 lm, 60000 lm, 50 W, 3000K/4200K/6500K, 110°, Safety class I, Mounting bracket

The SmartBright All-in Floodlight comes with a compact and sturdy design. It's a new range with robust die-cast aluminum housing suitable for general outdoor application. CCT selectable is involved that is more convenient for customers' different requirements, saving more time for product selection.

### Product data


General Information		Color rendering index (CRI)	
Number of gear units	1 unit	Color rendering index (CRI)	80
Gear	-	Number of light sources	1
Driver included	Yes	Beam angle of light source	110 degree(s)
Light source engine type	LED	Light source color	3000K/4200K/6500K
CE mark	No	Optic type	Wide beam
Warranty period	3 years	Optical cover type	Glass
Flammability mark	For mounting on normally flammable surfaces	Luminaire light beam spread	110°
ENEC mark	-	Operating and Electrical	
Glow-wire test	Temperature 650 °C, duration 30 s	Input Voltage	220 to 240 V
EU RoHS compliant	No	Line Frequency	50 or 60 Hz
		Inrush current	1.68 A
		Inrush time	0.0082 ms
		Power Consumption	50 W
		Power Factor (Fraction)	0.9
		Connection	Flying leads/wires
		Cable	Cable 1.0 m without plug 3-pole
Light Technical			
Luminous Flux	5,500 60,000 lm		
Correlated Color Temperature (Nom)	3000 4200 6500 K		
Luminous Efficacy (rated) (Nom)	110 120 lm/W		

# SmartBright All-in Floodlight

Number of products on MCB of 16 A type B 44	
<b>Temperature</b>	
Ambient temperature range	-25 to +40 °C
<b>Controls and Dimming</b>	
Dimmable	No
Control interface	-
<b>Mechanical and Housing</b>	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Housing Color	Grey
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	232 mm
Overall width	174 mm
Overall height	30 mm
Effective projected area	0.028 m <sup>2</sup>
Dimensions (Height x Width x Depth)	30 x 174 x 232 mm
<b>Approval and Application</b>	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

Photobiological risk specification	0.2 m
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.44, 0.40) SDCM <5;(0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%
<b>Application Conditions</b>	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable
<b>Product Data</b>	
Order product name	BVP158 LED60/WW_NW_CW PSU 50W SWB GM
Full product name	BVP158 LED60/WW_NW_CW PSU 50W SWB GM
Full product code	872016973277399
Order code	911401874286
Material Nr. (12NC)	911401874286
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169732773
Numerator - Packs per outer box	16
EAN/UPC - Case	8720169732858

## Dimensional drawing



## SmartBright All-in Floodlight

