



# SmartBright All-in Floodlight

## BVP158 LED180/WW\_NW\_CW PSU 150W SWB GM

SmartBright All-in Floodlight, 16500 lm, 18000 lm, 150 W, 3000K/4200K/6500K, 110°, Safety class I, Mounting bracket

The SmartBright All-in Floodlight comes with a compact and sturdy design. It's a new range with robust die-cast aluminum housing suitable for general outdoor application. CCT selectable is involved that is more convenient for customers' different requirements, saving more time for product selection.

### Product data

General Information		Luminaire light beam spread	
Number of gear units	1 unit		110°
Gear	-	Operating and Electrical	
Driver included	Yes	Input Voltage	220 to 240 V
Light source engine type	LED	Line Frequency	50 or 60 Hz
Light Technical		Inrush current	4.16 A
Luminous Flux	16,500 18,000 lm	Inrush time	0.0264 ms
Luminous Efficacy (rated) (Nom)	110 120 lm/W	Power Consumption	150 W
Correlated Color Temperature (Nom)	3000 4200 6500 K	Power Factor (Fraction)	0.9
Color rendering index (CRI)	80	Connection	Flying leads/wires
Number of light sources	1	Cable	Cable 1.0 m without plug 3-pole
Beam angle of light source	110 degree(s)	Number of products on MCB of 16 A type B 15	
Light source color	3000K/4200K/6500K	Temperature	
Optic type	Wide beam	Ambient temperature range	-25 to +40 °C
Optical cover type	Glass		

# SmartBright All-in Floodlight

## Controls and Dimming

Dimmable	No
Control interface	-

## Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover material	Tempered glass
Housing Color	Grey
Mounting device	Mounting bracket
Optical cover finish	Clear
Overall length	401 mm
Overall width	282 mm
Overall height	37 mm
Effective projected area	0.077 m <sup>2</sup>
Dimensions (Height x Width x Depth)	37 x 282 x 401 mm

## Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	No
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

Photobiological risk specification	0.2 m
EU RoHS compliant	No

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.44, 0.40) SDCM <5;(0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%


## Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

## Product Data

Order product name	BVP158 LED180/WW_NW_CW PSU 150W SWB GM
Full product name	BVP158 LED180/WW_NW_CW PSU 150W SWB GM
Full product code	872016973274299
Order code	911401877286
Material Nr. (12NC)	911401877286
Numerator - Quantity Per Pack	1
Net Weight (Piece)	3.290 kg
EAN/UPC - Product/Case	8720169732742
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169732827

## Dimensional drawing



## SmartBright All-in Floodlight

