

CAL5-11

[Print View..](#)**General Information**

Extended Product Type:	CAL5-11
Product ID:	1SBN010020R1011
EAN:	3471522121073
Catalog Description:	CAL5-11

Additional Information

Technical Information:	AUXILIARY SWITCH
CSA Certificate:	CSA_1033838
Core Credit:	0.00
Customs Tariff Number:	85369085
Data Sheet, Technical Information:	1SBC100122C0201-Ch04
Declaration of Conformity - CE:	1SBD250801C3000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
E-number:	E3228820
EAN:	3471522121073
Instructions and Manuals:	FPTC407744P0001
Invoice Description:	CAL5-11
Maximum Electrical Switching Frequency:	1200 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	A9 ... A75 10 million A95 ... A110 3 million A145 ... AF750 2 million
Minimum Order Quantity:	2 piece
Minimum switching capacity [V/mA]:	A9 ... A75 17 / 5 volt per milliamp A95 ... AF750 24 / 50 volt per milliamp
Mounting Position:	Side
Mounting on Contactors:	A 9...A 110
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Object Classification Code:	K
Package Level 1 Gross Weight:	0.08 kg
Package Level 1 Units:	2 piece
Part Type:	New
Power Loss:	Per Pole 0.1 W
Product Main Type:	CAL5-11
Product Net Depth:	62 mm
Product Net Height:	74 mm
Product Net Weight:	0.050 kg
Product Net Width:	12 mm
Rated Breaking Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Frequency (f_r):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690.0 V acc. to UL/CSA 600.0 V
Rated Making Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15



Rated Operational Current AC-15 (I_a):	(220 / 240V) 4 A (24 / 127V) 6 A (380 / 440V) 3 A (500V) 2 A (690V) 2 A
Rated Operational Current DC-13 (I_a):	(125V) 0.55 / 69 A (24V) 6 / 144 A (250V) 0.3 / 75 A (48V) 2.8 / 134 A (72V) 1 / 72 A
Rated Operational Voltage (U_e):	Auxiliary Circuit 690 V Main Circuit 24 V
Rated Short-time Withstand Current (I_{cw}):	for 1.0s 140.0 A
Remarks:	100
RoHS Information:	1SBD350058R1000
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
UL Certificate:	UL_071301E48139
