

CRC Brakleen Fast Dry

I. Product Description

CRC Brakleen Fast Dry is a powerful non-chlorinated solvent blend with superior cleaning and degreasing properties. It is formulated to quickly and safely remove brake fluid, grease, oil, hardened deposits and other contaminants from brake and clutch parts and all other mechanical components.

CRC Brakleen Fast Dry reduces disc-brake squeal and clutch chatter and helps brakes last longer and perform better. It is perfect for cleaning machinery, motors and general mechanical equipment when a vapour degreaser is required.

II. Features & Benefits

- Fast evaporation Minimises downtime
- Residue free Prevents harmful build up and eliminates rinsing or wiping
- Low surface tension Gives excellent penetration and ensures superior dissolving and degreasing properties
- Stable, non-staining, non-corrosive to metals
- Safe on most plastics, coatings and rubbers (test prior to use)
- Safely settles and removes brakes dust
- Works without disassembly
- Superior cleaning and degreasing properties that have many uses beyond brakes

III. Directions for Use

- Apply liberally and allow excess to run off.
- Air dry or dry with absorbent cloth.
- Repeat if necessary.
- After application, re-lubricate with CRC 5.56 if necessary.

Note: Check plastics and rubber compatibility before use. Do not use on sensitive electronics, use one of CRC's precision cleaners for these applications. Use with adequate ventilation. Do not use on energised equipment. Allow to dry thoroughly and vent before reactivating system.

IV. Typical Properties and Characteristics

Flash Point (bulk)	0℃
Flash Point (aerosol)	0°C
Appearance	Odourless liquid
Odour	Petroleum solvent
Vapour Density	3
Boiling Point	55-120℃
Solubility	Neg. in water
Specific Gravity	0.72
% Volatiles	100
Flammability	Flammable
Propellant (aerosol)	Carbon Dioxide



CRC Brakleen Fast Dry

V. Package Description

Part Number Size

5092 Jerry Can 20L 5083 Aerosol 600ml

VI. Special Precautions

General:

Highly flammable liquid and vapour. Extremely flammable aerosol. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/ ... /equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. Store in a well-ventilated place. Store locked up. Keep cool. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50 °C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Do not induce vomiting. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol.

Skin – Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. Eyes – Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention.

Inhalation – Remove from contaminated area. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 02/2012

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.