

Recessed Smart Tilt Downlight Kit  
**LEDE Economy Select 3K/4K**



**R773**



**SPECIFICATIONS**

<b>DIMENSIONS</b>	D103 x H54mm
<b>CUT OUT</b>	Ø 92mm
<b>COLOUR TEMP</b>	Selectable 3000K Warm White or 4000K Natural White
<b>LUMENS</b>	<b>White:</b> 3000K Warm White 800lm 4000K Natural White 850lm <b>Black:</b> 3000K Warm White 700lm 4000K Natural White 750lm
<b>CRI</b>	90
<b>LIFESPAN</b>	55,000 hours (L80 B20)
<b>BEAM ANGLE</b>	90°
<b>TILT ANGLE</b>	25° (Patented IP44 smart tilt gasket)
<b>MATERIAL</b>	Aluminium, ADC12, PBT, PC
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC-F Rated
<b>DRIVER</b>	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 180mA
<b>APPLICATION</b>	Residential / Commercial Interior
<b>WARRANTY</b>	5 Year Warranty

<b>&lt;850 LUMENS</b>	<b>8 WATTS</b>	<b>AC 240V</b>
---------------------------	--------------------	--------------------

	UID™ Dimmable Under Insulation Driver Included
--	--

select CCT

**AVAILABLE IN**

DESCRIPTION	CODE
Black 3000K/4000K Tilt "Select" Dual Colour	R773 B34V3
White 3000K/4000K Tilt "Select" Dual Colour	R773 W34V3