

Recessed Fixed Downlight Kit
LEDE Economy Select 3K/4K



SPECIFICATIONS

DIMENSIONS	D86 x H43mm
CUT OUT	Ø 72mm
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	White: 3000K Warm White 680lm 4000K Natural White 700lm Black: 3000K Warm White 570lm 4000K Natural White 590lm
CRI	90
LIFESPAN	55,000 hours (L80 B20)
BEAM ANGLE	90°
MATERIAL	Aluminium, ADC12, PBT, PC
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F Rated
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 200mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

<700 LUMENS	7 WATTS	AC 240V
---------------------------	--------------------	--------------------

	UID™ Dimmable Under Insulation Driver Included
--	--

select CCT

AVAILABLE IN

DESCRIPTION	CODE
Black 3000K/4000K "Select" Dual Colour	R770 B34V3
White 3000K/4000K "Select" Dual Colour	R770 W34V3