



SPECIFICATIONS

DIMENSIONS	D260 x H85mm
COLOUR TEMP	Selectable 3000K or 4000K
LUMENS	3000K: 4.5W/510lm, 9W/990lm 4000K: 4.5W/560lm, 9W/1050lm (Default factory setting 4000K/9W)
CRI	80
LIFESPAN	60,000 hours (L90 B50)
BEAM ANGLE	120°
MATERIAL	PC
IP RATING	IP54
IMPACT RATING	IK10
DRIVER	Incorporated, non-dimmable
ELECTRICAL CLASS	Class II - double insulated
APPLICATION	Interior Vertical or Horizontal Surface Mount
WARRANTY	5 Year Warranty

<1050
LUMENS

<9
WATTS

AC
240V

LEDE Commercial Buttons are modular in design, meaning all components are easily replaced quickly and with minimal waste. Hinged diode board and driver can be easily unplugged, removed and replaced. Ideal for retirement homes or easy maintenance for 24/7 commercial operations. See plug & play spare parts below for more details.

AVAILABLE IN

DESCRIPTION	CODE
White, "Select" 3000K/4000K, Dual Wattage	LED363 W34A




Suitable for multiple wiring configurations the LED363 also features dual side knockouts and dual rear cable glands.



PLUG & PLAY SPARE PARTS

DESCRIPTION	CODE
Replacement diffuser	LED363 DIFF
Replacement LED & driver module 3K/4K	LED363 34RBDM
Replacement driver	LED363 DR



LED363 DIFF

LED363 34RBDM

LED363 DR