

LEDE



SPECIFICATIONS

DIMENSIONS	D200 x H43mm
CUT OUT	N/A (Surface Mount)
COLOUR TEMP	Selectable 3000K Warm White or 4000K Natural White
LUMENS	Selectable 10W / 1100lm or 15W / 1650lm (default factory setting)
CRI	80
LIFESPAN	54,000 hours (L80 B50)
BEAM ANGLE	110°
MATERIAL	PC
IP RATING	IP54
IMPACT RATING	IK10
DRIVER	Incorporated, dimmable
ELECTRICAL CLASS	Class II - double insulated
APPLICATION	Horizontal Surface Mount
POWER FACTOR	0.95
WARRANTY	5 Year Warranty

AVAILABLE IN

DESCRIPTION	CODE
White 3000K/4000K "Select" Dual Colour, Dual Wattage	LED290 W34A
Black 3000K/4000K "Select" Dual Colour, Dual Wattage	LED290 B34A

<1650
LUMENS

<15
WATTS

AC
240V

INSTALLATION LEDE Quick Mount System

1. Mount base to the ceiling and connect mains to extra large terminal block.
2. Select wattage and colour temperature (Default factory settings: 15W, 3000K)
3. Connect lamp and driver via quick connect plug.
4. Push and turn module onto base clockwise to lock in place and tighten safety locking screw.

