



SPECIFICATIONS

DIMENSIONS	D100 x H101mm
CUT OUT	Ø 85-92mm
COLOUR TEMP	2700K, 3000K or 4000K
CRI	90 (R9 >60)
LIFESPAN	60,000 hours (L80 B30)
BEAM ANGLE	50°
TILT ANGLE	32°
MATERIAL	Aluminium + PC
IP RATING	IP54 (Complete with patented tilt gasket)
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC-F / IC-4
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 230mA
APPLICATION	Residential / Commercial Interior
WARRANTY	5 Year Warranty

840 LUMENS	9.5 WATTS	AC 240V
-------------------	------------------	----------------

	UID™ Dimmable Under Insulation Driver Included
---	--

AVAILABLE IN

DESCRIPTION	CODE
White 2700K	R750 W27K2
White 3000K	R750 W3K2
White 4000K	R750 W4K2
Black 2700K	R750 B27K2
Black 3000K	R750 B3K2
Black 4000K	R750 B4K2

ACCESSORIES

DESCRIPTION	CODE
White Flush fit adaptor plate kit for 100-135mm cut outs (145mm OD)	R750-W-AP145
Black Flush fit adaptor plate kit for 100-135mm cut outs (145mm OD)	R750-B-AP145

