



**R100** Standard

<b>Dimensions</b> D108 x H86mm	<b>Cut Out</b> Ø 92mm
<b>Watts</b> Selectable 7.2W, 9.2W or 11W	<b>Lumens</b> <1100lm
<b>Beam</b> 60° or 36°	<b>Tilt</b> 20° <b>Rotate</b> 360°



**R102** Offset


<b>Dimensions</b> D106 x H99mm	<b>Cut Out</b> Ø 92mm
<b>Watts</b> Selectable 7.2W, 9.2W or 11W	<b>Lumens</b> <1100lm
<b>Beam</b> 60° or 36°	<b>Tilt</b> 20° <b>Rotate</b> 360° <b>Offset</b> 25°

**Specifications**

Input	240V AC
Colour Temp	Selectable 3000K or 4000K
CRI	90 (R9<72)
Lifespan	60,000hrs (L80 B30)
Binning	SDCM 3
Material	Aluminium, PC, PA
IP Rating	IP44
Clearance	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
Classification	IC-F / IC-4
Driver	Included, DX Series Under Insulation
Dimming/Control	Phase-cut Dimmable
TLAs	"Flicker-free", PstLM≤1.0; SVM ≤0.4
Application	Interior, recessed
Warranty	5 Year Warranty

**Lumens**

	Finish	7.2W/200mA	9.2W/260mA	11W/300mA
R100	White	<800lm	<950lm	<1100lm
	Black	<750lm	<900lm	<1000lm
R102	White	<750lm	<950lm	<1100lm
	Black	<700lm	<850lm	<900lm



White

Black

**Available In**

Description	Code
<b>R100 - Standard</b>	
White, 60°	R100-W34KA-D-60D
White, 36°	R100-W34KA-D-36D
Black, 60°	R100-B34KA-D-60D
Black, 36°	R100-B34KA-D-36D
<b>R102 - Offset</b>	
White, 60°	R102-W34KA-D-60D
White, 36°	R102-W34KA-D-36D
Black, 60°	R102-B34KA-D-60D
Black, 36°	R102-B34KA-D-36D



Pre-wired with GL240 adaptor