

TECHNICAL DATA SHEET

MULTI-CORE SECURITY CABLE (TINNED)



Product Code	Description
MSEC 4072/100 TCW	4C 0.22mm (7/0.2) ACA3166 TCW SECURITY CABLE REEL 100M
MSEC 4072/300 TCW	4C 0.22mm (7/0.2) ACA3166 TCW SECURITY CABLE BOXES 300M
MSEC 4142/100 TCW	4C 0.44mm (14/0.2) ACA3166 TCW SECURITY CABLE REEL 100M
MSEC 4142/300 TCW	4C 0.44mm (14/0.2) ACA3166 TCW SECURITY CBLE 300M
MSEC 6072/100 TCW	6C 0.22mm (7/0.2) ACA3166 TCW SECURITY CABLE REEL 100M
MSEC 6072/300 TCW	6C 0.22mm (7/0.2) ACA3166 TCW SECURITY CABLE BOX 300M
MSEC 6142/100TCW	6C 0.44mm (14/0.2) ACA3166 TCW SECURITY CABLE REEL 100M
MSEC 6142/300TCW	6C 0.44mm (14/0.2) ACA3166 TCW SECURITY CABLE BOXES 300M
MSEC 8142/100 TCW	8C 0.44mm (14/0.2) ACA3166 TCW SECURITY CABLE 100M
MSEC 8142/250 TCW	8C 0.44mm (14/0.2) ACA3166 TCW SECURITY CABLE 250M

	4 CORE 0.22mm ²	4 CORE 0.44mm ²	6 CORE 0.22mm ²	6 CORE 0.44mm ²	8 CORE 0.44mm ²
Conductor:	Tinned Copper (AS1125) Ø=7*0.2±0.005mm*4	Tinned Copper (AS1125) Ø=14*0.2±0.005mm*4 32AWG	Tinned Copper (AS1125) Ø=7*0.2±0.005mm*6	Tinned Copper (AS1125) Ø=14*0.2±0.005mm*6 32AWG	Tinned Copper (AS1125) Ø=14*0.2±0.005mm*8 32AWG
Insulation:	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) Ø=1.25±0.05mm*4 PVC Colour: Red, Blue, White, Black	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) Ø=1.5±0.05mm*4 PVC Colour: Red, Blue, White, Black	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) Ø=1.25±0.05mm*6 PVC Colour: Red, Blue, White, Black, Green, Yellow	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) Ø=1.5±0.05mm*6 PVC Colour: Red, Blue, White, Black, Green, Yellow	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) Ø=1.5±0.05mm*8 PVC Colour: Red, Blue, White, Black, Green, Yellow, Brown, Violet
Outer Jacket:	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) PVC Colour: White Jacket thickness: 0.60±0.05mm Ø=4.10±0.10mm	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) PVC Colour: White Jacket thickness: 0.60±0.05mm Ø=4.5±0.10mm	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) PVC Colour: White Jacket thickness: 0.60±0.05mm Ø=4.70±0.10mm	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) PVC Colour: White Jacket thickness: 0.60±0.05mm Ø=5.70±0.10mm	PVC ROHS 75°C Flame Retardant (AS/NZS 3808) PVC Colour: White Jacket thickness: 0.70±0.05mm Ø=6.15±0.10mm
Packaging:	100M Red Plastic Reel, 5Reels/Box 300M Reel In Box	100M Red Plastic Reel, 5Reels/Box 300M Reel In Box	100M Red Plastic Reel, 5Reels/Box 300M Reel In Box	100M/Red Plastic Reel, 5Reels/Box 300M Reel In Box	100M Red Plastic Reel 250M Reel In A Box
Markings:	MASER SECURITY SOLUTIONS MSEC4072 0.22mm ² ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M	MASER SECURITY SOLUTIONS MSEC4142 0.44mm ² ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M	MASER SECURITY SOLUTIONS MSEC6072 0.22mm ² ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M	MASER SECURITY SOLUTIONS MSEC6142 0.44mm ² ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-300M	MASER SECURITY SOLUTIONS MSEC8142 0.44mm ² ACA3166 SECURITY CABLE EXTRA LOW VOLTAGE DD/MM/YYYY 001M-100M-250M