

# HEX BUNGS

# Metric/Pg



## Hard nylon threaded hex head bungs Strong and durable

### SPECIAL FEATURES

- Thick wall that can be drilled and tapped
- Reduce from large holes to small holes with minimum protrusion
- No slots or recesses to collect dirt
- Excellent mechanical properties

#### Metric

Thread	 mm	 mm	 mm	Pack size	Cat No
M12 x 1.5	12	8	18	50	HB12
M16 x 1.5	16	10	18	50	HB16
M20 x 1.5	20	12	24	50	HB20
M25 x 1.5	25	12	30	25	HB25
M32 x 1.5	32	12	36	25	HB32
M40 x 1.5	40	12	43	10	HB40
M50 x 1.5	50	12	53	5	HB50
M63 x 1.5	63	12	69	5	HB63

#### Pg

Thread	 mm	 mm	 mm	Pack size	Cat No.
Pg9	15.2	8	18	10	HBPG09
Pg11	18.6	10	22	10	HBPG11
Pg13.5	20.4	10	24	10	HBPG13
Pg16	22.5	10	27	10	HBPG16
Pg21	28.3	12	36	5	HBPG21
Pg29	37.0	12	43	5	HBPG29
Pg36	47.0	12	53	5	HBPG36

### TECHNICAL DATA

- Material:** Nylon  
**Colour:** Metric—Black or Grey/Pg—Black Only  
**Working temp:** -40°C to 100°C. Short term 130°C  
**Chemical resistance:** Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis, bases and salts.

Additional technical information available on request

Dimensions and specifications may be changed without notice.

A product designed and distributed by

## McCABE INDUSTRIES LTD

667C High Street, Lower Hutt 5010, New Zealand  
Ph: 045289619; Email: [info@mccabeindustries.co.nz](mailto:info@mccabeindustries.co.nz)  
[www.mccabeindustries.co.nz](http://www.mccabeindustries.co.nz)

