

Catalogue No: **[Cat No. not in MAX]**

**[Item name not in MAX]**

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - GRPC, ABS and PC > ARCA GRPC Wall Mount Enclosures > Mounting Plates Included



#### Enclosure Wall Mount ARCA PC IP66 H400xW300xD210mm W/MP

- Fully electrically insulated, corrosion proof and weighing up to 60% less than steel makes them a perfect alternative to stainless steel
- Easily customised and machined with easy to use accessories makes installation a dream
- UV protection according to UL 508 and IP66 rating ensures the ARCA enclosures stand the test of time in outdoor conditions
- IK10 impact protection rating provides excellent protection against vandalism
- Patented strong hinge design to withstand regular door opening to 120° and the fitting of door mounted components
- Compatible with the majority of NHP's existing standard enclosure locking options to ensure a secure solution for every application
- Patented lockable inner door – no tools required for mounting
- Patented easy to use DIN-rail frame set design – no special tools required – easy and quick mounting
- Mounting pods on the base, cover and four base sides
- Variable depth option for internal plates
- Double corner design with mounting holes outside the ingress protected area
- Option for steel or insulated mounting plates

Representative Photo Only  
(actual product may vary based on configuration selections)

#### SPECIFICATIONS

Product Series	ARCA
Material, Body / Housing	Glass Reinforced Polycarbonate material
Glow Wire Rating	IEC 60695-2-1 960°C
Flammability Rating (UL94)	UL 94 5VA
UV Rating	UL 508
Halogen Free	Yes
Short Term Temperature, Min	-40 °C
Short Term Temperature, Max	120 °C
Continuous Temperature, Min	-40 °C
Continuous Temperature, Max	80 °C
Colour, Cover	Light Grey (RAL 7035) colour
Colour, Body / Housing	Light Grey (RAL 7035) colour
IP Rating	IP66
IK Rating	IK10
Insulation Class	II
Mounting Plate Included	Yes
Material Thickness, Mounting Plate / Bracket	4.5 mm
Material, Gasket / Seal	PUR / PU material
Lock Type	DIN - 1/4 Turn type
Diameter, Lock	3 mm
Material, Lock	Plastic material

Catalogue No: **[Cat No. not in MAX]**

**[Item name not in MAX]**

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > Wall Mount Enclosures - GRPC, ABS and PC > ARCA GRPC Wall Mount Enclosures > Mounting Plates Included



Standards Compliance	EN 60529 EN 62262 EN 62208 EN 61439-1-4 IEC 62208 EU RoHS directive 2011/65/EU EC Low voltage directive 2006/95/EC (up to 1500V DC)
Certifications	SGS Fimko GOST-R

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-