



16MM RECTANGULAR MOMENTARY PUSH/PULL PUSHBUTTON



- 800B 16 mm operators are perfect for your light industrial and instrumentation application needs with their highly configurable and flexible design.
- Small in size, these operators are excellent for applications with limited panel space or a small footprint.
- Made of corrosion-proof plastic that is suitable for harsh environments and ensures long push button life. Consistent coloring and illumination makes these easy to identify for the life of the operator.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Pushbutton and Pilot Lights	Pushbutton
RoHS Approved	Yes
CE Marked	Yes
Operating Temperature, Max	-25 °C max
Operating Temperature, Min	55 °C min
Storage Temperature, Max	-40 °C max
Storage Temperature, Min	70 °C min
Relative Humidity, Min	50 %RH
Relative Humidity, Max	95 %RH
IP Rating	IP66
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 m/s ²
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	360 min
Standards Compliance	UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1
Certifications	CSA CCC CE UR RoHS

Catalogue No: **800B-EPC**

PB/PL 16mm EXT MOM OPERATOR RECTANGULAR BEZEL

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800B Pushbuttons > 800B Pushbuttons



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -