

Catalogue No: 802T-APE

SPR-RTN-LVR IP67 1NO/1NC CW/CCW 0.29NM 13DEG LO-TEMP

Field Switching and Sensing > Limit Switch > Limit Switches > Allen-Bradley Limit Switches > Bulletin 802T General Purpose Limit Switches > Lever Type Switches



Limit Switch, NEMA Type 4 and 13 Oiltight Construction, Plug-In, Lever Type, Spring Return, Standard Operating Torque, 2-Circuit, CW and CCW operation, Low Temperature Operation

- Factory sealed versions for demanding industrial environments
- Complete range of IEC style solutions for both safety and standard sensing applications
- Wide range of operating voltages and current ratings
- Extensive range of different housing styles and mounting options
- Wide variety of operating heads and levers

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	802T Low-Energy
Component Type Field Switching & Sensing	Limit Switch, Complete, No Operator
Contact Configuration	1 NO + 1 NC EB 1st Contact
Contact Action	Snap Action action
Actuator Action	Spring Return action
Conduit Entry	1/2" - 14NPT entry
Material, Body / Housing	Metal material
Height	103.33 mm
Width	41.28 mm
Depth	71.21 mm
Safety Application Suitable	No
Operating Temperature, Max	110 °C max
Operating Temperature, Min	-18 °C min
IP Rating	IP67

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-