



### Main

|                           |               |
|---------------------------|---------------|
| Range                     | PDL Iconic    |
| Product or component type | Rotary dimmer |
| Device presentation       | Mechanism     |

### Complementary

|                                     |                                                                                                                                                                                                                                                                                                        |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device mounting                     | Clip with locking bar                                                                                                                                                                                                                                                                                  |
| Range compatibility                 | PDL Iconic                                                                                                                                                                                                                                                                                             |
| Actuator                            | Rotary                                                                                                                                                                                                                                                                                                 |
| Fixing mode                         | Clip-in                                                                                                                                                                                                                                                                                                |
| Colour tint                         | Vivid white                                                                                                                                                                                                                                                                                            |
| Surface finish                      | Glossy                                                                                                                                                                                                                                                                                                 |
| Type of packing                     | Box                                                                                                                                                                                                                                                                                                    |
| Sale per indivisible quantity       | 1                                                                                                                                                                                                                                                                                                      |
| Ambient air temperature for storage | 0...60 °C                                                                                                                                                                                                                                                                                              |
| Dimmer control                      | 315° rotary setting                                                                                                                                                                                                                                                                                    |
| [Ie] rated operational current      | 1.5 A                                                                                                                                                                                                                                                                                                  |
| [Ue] rated operational voltage      | 220...240 V AC 50 Hz                                                                                                                                                                                                                                                                                   |
| Load type                           | Dimmable LED 350 W (240 V AC)<br>Incandescent 350 W (240 V AC)<br>Low voltage halogen lamp with electronic transformer 350 W (240 V AC)<br>Dimmable fluocompact lamp 150 W (240 V AC)<br>Low voltage halogen lamp with iron core transformer 350 W (240 V AC)<br>Dimmable fluorescent 150 W (240 V AC) |
| Derating factor                     | Number of devices 1 without derating<br>Number of devices 2 with derating<br>Number of devices 3 with derating                                                                                                                                                                                         |
| Function available                  | Brightness adjustment                                                                                                                                                                                                                                                                                  |
| Protection type                     | Short-circuit                                                                                                                                                                                                                                                                                          |
| Protection type                     | Current overload<br>Thermal protection internal fuse without reset<br>Short-circuit<br>Thermal overload protection                                                                                                                                                                                     |
| Remote control type                 | Without                                                                                                                                                                                                                                                                                                |
| Connections - terminals             | Flying leads                                                                                                                                                                                                                                                                                           |

|                 |                                                          |
|-----------------|----------------------------------------------------------|
| Material        | PC (UL94 V-2) for top<br>PC MAS056 (UL94 V-2) for bottom |
| Height          | 22.5 mm                                                  |
| Width           | 22.5 mm                                                  |
| Depth           | 39 mm                                                    |
| Embedding depth | 37 mm                                                    |
| Standards       | AS/NZS 60669.2.1                                         |

## Environment

|                                       |           |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity                     | 0...90 %  |

## Offer Sustainability

|                        |                                                                                                                                                                                                                         |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoHS (date code: YYWW) | Compliant - since 1713 - Schneider Electric declaration of conformity<br> <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                  | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                                                                                                  |