

Product data sheet

Characteristics

PDL56PB2LEGY

Momentary Push Button Switch, IP66, 2 Button



Main

Range of product	56 Series
Product or component type	Push-button switch
Control type	Push-button latching
Colour tint	Grey

Complementary

Material	PC (polycarbonate)
Surface finish	Gloss
Installation direction	Horizontal/vertical
Width	95 mm
Height	95 mm
Depth	20 mm
[In] rated current	16 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Device mounting	Surface
Fixing center	84 x 84 mm
IP degree of protection	IP67
Ambient air temperature for operation	-40...55 °C
Cable cross section	0.75...6 mm ²
Auxiliary contact composition	1 NO/NC
Quantity per set	Set of 8
Type of packing	Carton

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	9.5 cm
Package 1 Length	9.5 cm
Package 1 Weight	0.121 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile