

## Product data sheet

### Characteristics

# PDL570SWH

## Mount Unswitched Shuttered Socket, 10A, 250V



### Main

Range of product	PDL General Accessories
Product or component type	Socket
Colour tint	White

### Complementary

Material	PC (polycarbonate)
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	250 V 50 Hz
Network number of phases	1 phase
Socket number	3
Installation direction	Vertical
Height	50.8 mm
Width	50.8 mm

### Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	5.3 cm
Package 1 Length	5.5 cm
Package 1 Weight	50 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

---

China RoHS Regulation

 [China RoHS Declaration](#)

---

Environmental Disclosure

 [Product Environmental Profile](#)

---