

Product data sheet

Characteristics

PDL570RWH

Flush Unswitch Shuttered Socket, General Accessories, 10A, 250V



Main

Range of product	PDL General Accessories
Product or component type	Socket
Colour tint	White
Quantity per set	Set of 10
Type of packing	Carton

Complementary

Material	PC (polycarbonate)
Surface finish	Glossy
[In] rated current	10 A
[Ue] rated operational voltage	250 V 50 Hz
Network number of phases	1 phase
Socket number	3
Installation direction	Vertical
Mounting support	Panel
Depth	17.5 mm
Diameter	57 mm
Fixing center	34 mm

Environment

Ambient air temperature for operation	-10...40 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	5.5 cm
Package 1 Length	5.5 cm
Package 1 Weight	0.051 kg

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
