

Product data sheet

Characteristics

PDLO381-BK

Switch, PDL Iconic, 20A/16AX, 250 V, 1 Gang, horizontal, Black



Main

Range of product	Iconic
Range of product	PDL Iconic
Product or component type	Switch
Product brand	PDL
Device application	Lighting
Device presentation	Complete product
Colour	Black (BK)

Complementary

Device mounting	Surface
Switch function	1-pole 1/2-way
Number of gangs	1 gang
Number of rocker	1
Actuator	Rocker
Fixing mode	By screws By clipping locks
Surface finish	Matt
Surface treatment	Untreated
Rated current	20 A at 250 V AC 50 Hz 16 AX at 250 V AC 50 Hz
Electrical durability	12000 cycles
Connections - terminals	4 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Phillips No 2
Clamping connection capacity	4 x 1.5 mm ² 3 x 2.5 mm ²
Wire stripping length	10 mm
Local signalling	Without
Material	PC (polycarbonate) TPE (thermoplastic elastomer) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Height	85 mm
Width	115.5 mm
Depth	70 mm
Net weight	0.19 kg

Environment

Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Standards	AS/NZS 3133
IP degree of protection	IP56

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Halogen content performance	Halogen free plastic parts product