

## Product data sheet

### Characteristics

# PDL395USBC-VW

## PDL Iconic, Twin Socket USB Type C Fast, 25W



### Main

|                            |                                  |
|----------------------------|----------------------------------|
| Range                      | PDL Iconic                       |
| Product or component type  | Switched socket with USB charger |
| Device presentation        | Complete product                 |
| Product brand              | PDL                              |
| Switch application         | Control                          |
| Outlet poles configuration | 2P + E with shutter              |
| Outlet standard            | Australian                       |

### Complementary

|                                |   |
|--------------------------------|---|
| Device mounting                | Flush   |
| Mounting position              | Horizontal  |
| Number of power socket outlets | 2   |
| Number of rocker               | 2   |
| Range compatibility            | Iconic switched socket with USB charger   |
| Outlet standard description    | With earthing contact   |
| Outlet standard                | Australian/New Zealand  |
| Ground lug position            | Straight 180° position  |
| Pin number                     | 3   |
| Fixing mode                    | By screw  |
| Installation direction         | Horizontal  |
| Colour                         | Vivid white (VW)  |
| Surface finish                 | Matt  |
| Type of packing                | Polybag   |
| Quantity per set               | 1 set of 10   |
| Sale per indivisible quantity  | 1   |
| Rated current                  | 10 A at 220...240 V AC 50 Hz  |
| Connections - terminals        | 3 screw terminals   |
| Screwdriver shape              | Square drive no 1 (SQ1)   |
| Clamping connection capacity   | 1 x 2.5...4 x 2.5 mm <sup>2</sup> for stranded cable(s)   |
| Wire stripping length          | 16 mm   |
| Material                       | PC (polycarbonate): cover frame<br>ABS (acrylonitrile butadiene-styrene): cover frame<br>PC (polycarbonate): fixing frame |
| Height                         | 120 mm  |
| Width                          | 78 mm   |
| Depth                          | 44 mm   |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for storage   | 0...60 °C   |
| Ambient air temperature for operation | 0...45 °C   |
| Relative humidity                     | 10...95 %   |
| Standards                             | AS/NZS 3112 |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 6.0 cm  |
| Package 1 Width              | 2.7 cm  |
| Package 1 Length             | 4.7 cm  |
| Package 1 Weight             | 105.0 g |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |