

Product datasheet

Specifications



Auxiliary contact, Acti9 A9N, OF, 1 C/O, 100mA to 6A, 24VAC to 415VAC, 24VDC to 130VDC, bottom connection

A9N26904

Main

| | |
|-----------------------------|--|
| Range Of Product | Acti9 |
| Product Or Component Type | OC contact |
| Device Short Name | OF |
| Signal Contacts Composition | 1 C/O |
| [In] Rated Current | 0.1...6 A at 24...250 V, AC 50/60 Hz 0.1...6 A at 24...240 V, AC 50/60 Hz 0.1...3 A at 415 V, AC 50/60 Hz 0.1...6 A at 24 V, DC 0.1...2 A at 48 V, DC 0.1...1.5 A at 60 V, DC 0.1...1 A at 130 V, DC |
| 9 Mm Pitches | 1 |

Complementary

| | |
|--|---|
| [Ui] Rated Insulation Voltage | 500 V |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV |
| Mounting Mode | Clip-on |
| Mounting Location | Left side of circuit-breaker |
| Mounting Support | DIN rail |
| Comb Busbar And Distribution Block Compatibility | Top: YES |
| Height | 85.3 mm |
| Width | 9 mm |
| Depth | 68 mm |
| Net Weight | 30 g |
| Colour | White |
| Connections - Terminals | Screw clamp terminal (bottom) 1 cable(s) 0.5...2.5 mm ² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible Screw clamp terminal (bottom) 2 cable(s) 1.5 mm ² - flexible with ferrule |
| Wire Stripping Length | 9 mm |
| Tightening Torque | 1 N.m bottom |

Environment

| | |
|------------------------|----------------------------------|
| Standards | EN/IEC 60947-5-1 GB/T 14048.5 |
| Product Certifications | CE UKCA |

| | |
|---------------------------------------|-------------|
| Quality Labels | EAC CCC |
| Ip Degree Of Protection | IP20 |
| Pollution Degree | 3 |
| Tropicalisation | 2 |
| Ambient Air Temperature For Operation | -25...70 °C |
| Ambient Air Temperature For Storage | -40...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 2.000 cm |
| Package 1 Width | 7.800 cm |
| Package 1 Length | 9.400 cm |
| Package 1 Weight | 36.700 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 8.500 cm |
| Package 2 Width | 10.000 cm |
| Package 2 Length | 26.600 cm |
| Package 2 Weight | 498.000 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 108 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 4.971 kg |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Circularity Profile

[End of Life Information](#)