



Main

| | |
|-------------------------------|-------------|
| Range | Resi9 |
| Product or component type | Comb busbar |
| Total number of 18 mm modules | 15 |

Complementary

| | |
|--|---|
| Number of ways | Outgoer: 13 ways N + L Incomer: 2 ways N + L |
| Poles configuration | Outgoer: 1P + N |
| Connection pitch | Incomer: 18 mm Outgoer: 9 mm |
| Insulation | Insulated |
| Device presentation | Cuttable |
| Provided components | 1 connector 5 tooth covers 1 neutral terminal block |
| [Ie] rated operational current | 100 A |
| [Ue] rated operational voltage | 230 V AC |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Mounting mode | Horizontal |
| Mounting location | Top |
| Colour | White (RAL 9003) |

Environment

| | |
|-----------------|-------------------------------|
| Standards | AS/NZS 61439-3 AS/NZS 3000 |
| Fire resistance | 960 °C |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 2.2 cm |
| Package 1 Length | 27.5 cm |
| Package 1 Weight | 230 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 24 cm |
| Package 2 Width | 29 cm |
| Package 2 Length | 33 cm |
| Package 2 Weight | 2.76 kg |

Offer Sustainability

| | |
|-----------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| China RoHS Regulation | China RoHS Declaration |