

Product Environmental Profile

ACTI9 RESIDUAL CURRENT BREAKER WITH OVERCURRENT PROTECTION




General information

Reference product	A9 iC60H3 3P+N _s C Curve 32A 30mA A RCBO - A9DC1932
Description of the product	This Acti9 RCBO product is designed for DIN rail distribution boards. This circuit breaker provides maximum protection and continuity of service while minimising service intervention time. It brings a safe and reliable solution for commercial and industrial applications.
Functional unit	<p>Protect the installation against overloads and short circuits and protect people and premises at risk of fire or explosion, against insulation defects in a circuit with IP20 in accordance with EN 60529. The specifications are used in the household / commercial application areas, according to the appropriate use scenario, during the reference service life of the product of 20 years. This protection is ensured in accordance with the following parameters:</p> <ul style="list-style-type: none"> - Rated voltage U_e: 415V - Rated current I_n: 32A - Number of poles N_p: 3+N, Neutral Unswitched - Rated breaking capacity I_{cn}: 10kA - Tripping curve Cd: C curve - Sensitivity S: 30 mA - Type of differential protection T_p: A

Constituent materials

Reference product mass	544 g including the product, its packaging and additional elements and accessories
------------------------	------------------------------------------------------------------------------------



Plastics	32.7%
Metals	42.8%
Others	24.5%

Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <https://www.se.com/ww/en/work/support/green-premium/>

Additional environmental information

End Of Life	Recyclability potential:	46%	Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Environmental impacts

Reference service life time	20 years		
Product category	Differential circuit breaker		
Installation elements	The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).		
Use scenario	Load rate: 15% of In 32A Use time rate: 30% of RLT 20 Years		
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product.		
Geographical representativeness	Australia		
Energy model used	[A1 - A3]	[A5]	[B6]
	Electricity Mix; Production mix; Low voltage; CN	Electricity Mix; Production mix; Low voltage; AUS	Electricity Mix; Production mix; Low voltage; AUS
			[C1 - C4]
			Electricity Mix; Production mix; Low voltage; AUS

Detailed results, including all the impact indicators mentioned in PCRed4 are available in the LCA report and on demand in a digital format - Country Customer Care Center <http://www.schneider-electric.com/contact>

Mandatory Indicators		ACT19 RESIDUAL CURRENT BREAKER WITH OVERCURRENT PROTECTION - A9DC1932						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Loads and Benefits [D]
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	
Contribution to climate change	kg CO2 eq	4.36E+01	4.82E+00	4.35E-02	7.68E-02	3.74E+01	1.23E+00	-9.78E-01
Contribution to climate change-fossil	kg CO2 eq	4.35E+01	4.80E+00	4.35E-02	7.33E-02	3.74E+01	1.22E+00	-9.63E-01
Contribution to climate change-biogenic	kg CO2 eq	5.73E-02	2.28E-02	0*	3.41E-03	1.82E-02	1.28E-02	-1.48E-02
Contribution to climate change-land use and land use change	kg CO2 eq	2.15E-07	3.90E-08	0*	1.10E-10	0*	1.75E-07	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	5.94E-07	3.92E-07	6.66E-11	5.08E-09	1.82E-07	1.51E-08	-2.37E-07
Contribution to acidification	mol H+ eq	2.94E-01	4.32E-02	2.90E-04	3.05E-04	2.46E-01	4.49E-03	-1.32E-02
Contribution to eutrophication, freshwater	kg (PO4) ³⁻ eq	4.49E-04	7.38E-05	0*	5.55E-07	2.65E-07	3.75E-04	-3.08E-06
Contribution to eutrophication marine	kg N eq	3.40E-02	5.24E-03	1.37E-04	8.07E-05	2.72E-02	1.43E-03	-6.67E-04
Contribution to eutrophication, terrestrial	mol N eq	3.73E-01	5.50E-02	1.50E-03	6.09E-04	3.08E-01	7.18E-03	-7.27E-03
Contribution to photochemical ozone formation - human health	kg COVNM eq	1.11E-01	1.76E-02	3.81E-04	1.63E-04	9.07E-02	2.18E-03	-3.01E-03
Contribution to resource use, minerals and metals	kg Sb eq	8.34E-04	8.23E-04	0*	0*	5.78E-07	1.05E-05	-2.16E-04
Contribution to resource use, fossils	MJ	6.93E+02	7.64E+01	6.06E-01	7.99E-01	5.78E+02	3.78E+01	-1.52E+01
Contribution to water use	m3 eq	2.02E+01	3.00E+00	0*	3.28E-02	1.48E+00	1.57E+01	-7.88E-01

Inventory flows Indicators		ACT19 RESIDUAL CURRENT BREAKER WITH OVERCURRENT PROTECTION - A9DC1932						
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits [D]
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	4.48E+01	8.01E-01	0*	5.73E-02	4.37E+01	3.21E-01	1.51E-01
Contribution to use of renewable primary energy resources used as raw material	MJ	8.36E-01	8.36E-01	0*	0*	0*	0*	-7.59E-01
Contribution to total use of renewable primary energy resources	MJ	4.57E+01	1.64E+00	0*	5.73E-02	4.37E+01	3.21E-01	-6.08E-01
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.86E+02	6.93E+01	6.06E-01	7.99E-01	5.78E+02	3.78E+01	-1.52E+01
Contribution to use of non renewable primary energy resources used as raw material	MJ	7.04E+00	7.04E+00	0*	0*	0*	0*	-9.34E-04
Contribution to total use of non-renewable primary energy resources	MJ	6.93E+02	7.64E+01	6.06E-01	7.99E-01	5.78E+02	3.78E+01	-1.52E+01
Contribution to use of secondary material	kg	1.74E-04	1.74E-04	0*	0*	0*	0*	0.00E+00

Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of freshwater	m³	5.15E-01	6.99E-02	0*	7.64E-04	3.45E-02	4.10E-01	-1.84E-02
Contribution to hazardous waste disposed	kg	1.89E+01	1.73E+01	0*	0*	9.54E-01	6.14E-01	-1.74E+01
Contribution to non hazardous waste disposed	kg	8.52E+00	2.07E+00	1.52E-03	2.50E-01	6.02E+00	1.88E-01	-1.48E+00
Contribution to radioactive waste disposed	kg	9.31E-04	2.94E-04	1.09E-06	3.35E-05	5.92E-04	1.06E-05	-2.36E-04
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	2.62E-01	4.24E-04	0*	4.22E-02	0*	2.20E-01	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version 5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, are available in the LCA report and on demand in a digital format - Country Customer Care Center <http://www.schneider-electric.com/contact>

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	ENVPEP2308033_V2	Drafting rules	PEP-PCR-ed4-2021 09 06
Validity period	5 years	Supplemented by	PSR-0005-ed3-EN-2023 06 06
Date of issue	03/2024	Information and reference documents	www.pep-ecopassport.org
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016			
Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>			
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)			
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021 : 2016 « Environmental labels and declarations. Type II environmental declarations »			

Schneider Electric Industries SAS
 Country Customer Care Center
<http://www.se.com/contact>
 35, rue Joseph Monier
 CS 30323
 F- 92500 Rueil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 928 298 512 €

www.se.com

ENVPEP2308033_V2

Published by Schneider Electric

©2023 - Schneider Electric – All rights reserved

03/2024