

# Product data sheet

Specifications



## Double switched socket, Pro Series, RCD, 10mA, 10A, horizontal, extra white

PDLP395RCD10V2-XW

### Main

Range	Pro Series
Product or component type	RCD socket
Device presentation	Complete product
Product brand	PDL
Outlet poles configuration	2P + E shutter
Outlet standard	Australian
Colour tint	White
Main colour tint	White

### Complementary

Socket-outlet type	Double socket-outlet
Control type	Rocker
Device mounting	Wall mounted
Number of power socket outlets	2
Number of rocker	2
Range compatibility	Pro Series
Outlet standard description	With earthing contact
Outlet standard deviation	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screws
Installation direction	Horizontal
Local signalling	LED indicator
Surface finish	Glossy
surface treatment	Untreated
Sale per indivisible quantity	1
Connections - terminals	3 screw terminals
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	1 x 2.5...4 x 2.5 mm <sup>2</sup> for rigid or stranded cable(s) 3 x 4 mm <sup>2</sup> for rigid or stranded cable(s)
Wire stripping length	16 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Material</b>	PC (polycarbonate): fixing frame PP (polypropylene) POM (polyoxymethylene): shutter PC (polycarbonate): window ABS (acrylonitrile butadiene-styrene): infill piece ABS (acrylonitrile butadiene-styrene): skin
<b>Height</b>	78.2 mm
<b>Width</b>	116 mm
<b>Fixing center</b>	84 mm
<b>Depth</b>	43.6 mm
<b>Net weight</b>	94 g
<b>Earth-leakage protection class</b>	Type I Type A
<b>Trip unit rating</b>	10 mA
<b>Network frequency</b>	50 Hz
<b>[Ue] rated operational voltage</b>	230...240 V
<b>Local signalling</b>	LEDs
<b>Rated current</b>	10 A
<b>Network type</b>	AC
<b>Connections - terminals</b>	Screw terminal
<b>Number of terminals</b>	3

## Environment

<b>Ambient air temperature for operation</b>	0...45 °C
<b>Relative humidity</b>	10...95 %
<b>Standards</b>	AS/NZS 3190 AS/NZS 3100 ISO 22196
<b>Product certifications</b>	RCM
<b>IK degree of protection</b>	IK08
<b>IP degree of protection</b>	IP20
<b>Environmental characteristic</b>	Indoor use

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.1 cm
<b>Package 1 Width</b>	8.1 cm
<b>Package 1 Length</b>	12.6 cm
<b>Package 1 Weight</b>	213 g
<b>Unit Type of Package 2</b>	CAR
<b>Number of Units in Package 2</b>	32
<b>Package 2 Height</b>	22.4 cm
<b>Package 2 Width</b>	26.1 cm
<b>Package 2 Length</b>	33.5 cm

<b>Package 2 Weight</b>	6.5 kg
<b>Unit Type of Package 3</b>	PAL
<b>Number of Units in Package 3</b>	1536
<b>Package 3 Height</b>	95 cm
<b>Package 3 Width</b>	114 cm
<b>Package 3 Length</b>	114 cm
<b>Package 3 Weight</b>	334.8 kg

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **181**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Recycled metal content at CR level **0**

[EU RoHS Directive](#) **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)