

Product data sheet

Specifications



RCD plate, Pro Series, 10mA, 20A, vertical/horizontal, extra white

PDLP396RCD10-XW

Main

Range of product	600 Series
Product or component type	RCD plate
surface treatment	Untreated
Colour tint	White

Complementary

Control type	Push-button
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Gloss
Installation direction	Horizontal/vertical
Width	78.2 mm
Height	116 mm
Rated current	20 A
[Ue] rated operational voltage	230...240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of poles	2
Mounting mode	Wall-mounted
Fixing center	84 mm
Cable cross section	4 x 2.5 mm ²
Earth-leakage protection class	Type I Type A
Earth-leakage sensitivity	10 mA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	8.1 cm
Package 1 Length	12.6 cm
Package 1 Weight	180 g
Unit Type of Package 2	CAR

Number of Units in Package 2	32
Package 2 Height	22.4 cm
Package 2 Width	26.1 cm
Package 2 Length	33.5 cm
Package 2 Weight	5.5 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1536
Package 3 Height	95 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	284.1 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Recycled metal content at CR level

0

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)