



## Main

Range	Acti 9
Device short name	ISW
Product or component type	Switch disconnecter
Switch application	Isolation Control
Poles description	1P
Utilisation category	AC-22A
Suitability for isolation	Yes

## Complementary

[Ie] rated operational current	100 A 240 V AC 50/60 Hz
[Ue] rated operational voltage	240 V AC 50/60 Hz
[Icm] rated short-circuit making capacity	5 kA switch-disconnector alone
[Icw] rated short-time withstand current	1500 A
[Ui] rated insulation voltage	250 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar distribution block compatibility	Top or bottom : YES
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	75.5 mm
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Connections - terminals	Tunnel type terminals: (top or bottom) 1 cable(s) <= 50 mm <sup>2</sup> rigid without cable end Tunnel type terminals: (top or bottom) 1 cable(s) <= 35 mm <sup>2</sup> flexible without cable end Tunnel type terminals: (top or bottom) 1 cable(s) <= 35 mm <sup>2</sup> flexible with cable end
Wire stripping length	9 mm
Tightening torque	3.5 N.m

## Environment

standards	EN 60947-3 IEC 60947-3 BS EN 60947-3 AS 60947-3 NZS 60947-3
IP degree of protection	IP20
pollution degree	3
tropicalisation	2
relative humidity	95 % at 55 °C
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1246 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations