

30USM-BK

UNIVERSAL MECHANISM 20A 16AX ROCKER.
30USM REPLACES 30FLM16, 30M15 AND
30M20OV. 30USM,BK REPLACES 30M16,BK,
30USM-3S REPLACES 30M20-3S AND
30FLM15,3S. 30USM,BG AND 30USM,DS
REPLACES 30M20,BG AND 30M20,DS. 30USM,BR
REPLACES 30FLM15,BR. 30USM,SG REPLACES
30



Main

Colour	Black
Product brand	Clipsal
Device presentation	Basic element

Complementary

Colour code	BK
Switch function	1-way 2-way
Actuator	Rocker
Number of rocker	1
Device mounting	Flush
Fixing mode	By screws
Local signalling	Without
[Ue] rated operational voltage	250 V AC
Rated current	20 A 16 AX fluorescent lamp
Marking	Without marking

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1250 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.