



Main

Product name	Easy56
Product or component type	Switch and socket-outlet
Device short name	EY56C315
Plug, socket category	Low voltage
Poles description	1P + N + E
Control type	Rotary knob
Rotary handle padlocking	2 padlocks x Ø 8 mm
Network type	AC
Outlet standard	Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	15 A
Pin number	3 pins
Shape of pin	Flat
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Phosphor bronze pins :
Connections - terminals	Screw terminals
Cable cross section	1.5...6 mm ²
Cable entry number	2 x M25 1 x M32
Product weight	0.82 kg
Height	203 mm
Width	101 mm
Depth	101 mm
Colour	Grey RAL 7035 body Dark grey rotary handle

Environment

standards	AS/NZS 3112 AS/NZS 3133
quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C
ambient air temperature for storage	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------