

## NSYTRR22

Lineryy passthrough terminal block - 2.5mm<sup>2</sup> 24A  
single-level 1x1 spring - grey



### Main

Range	Lineryy
Product name	Lineryy TR
Product or component type	Terminal block
Device short name	TRR
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	2.5 mm <sup>2</sup>
Length	48.5 mm
Colour	Grey
Quantity per set	Set of 50

### Complementary

Width	5.2 mm
Height	36.5 mm
Connections - terminals	1 x spring terminal : upstream 1 x spring terminal : downstream
Number of terminals	2
Connection position	Top
Number of measurement input	2
Cable cross section	0.08...2.5 mm <sup>2</sup> , flexible without cable end 0.08...4 mm <sup>2</sup> , solid with cable end 0.2...2.5 mm <sup>2</sup> , flexible with cable end 0.08...4 mm <sup>2</sup> , solid without cable end
Wire stripping length	10 mm
Tool type	Connection : flat screwdriver Disconnection : flat screwdriver
[U <sub>e</sub> ] rated operational voltage	800 V conforming to EN/IEC 60947-7-1 600 V CSA 600 V CSA 600 V cURus
[I <sub>e</sub> ] rated operational current	24 A conforming to EN/IEC 60947-7-1 20 A CSA 20 A CSA 20 A cURus
Material	Polyamide 6/6 (insulating case) Copper alloy (connector and screw) Copper alloy (commoning link) Chromium-nickel steel (spring)
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kV) conforming to IEC 60093 500 CTI (> 400 kV) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.8 mm conforming to UL 94
Product weight	5.6 g
Range compatibility	Prisma - G

Prisma - P  
Pragma  
Prisma - PH  
Prisma - Pack  
Spacial  
Kaedra  
TeSys

---

Product compatibility	Spacial enclosures
-----------------------	--------------------

---

## Environment

---

product certifications	ATEX CSA CURus DNV GL LR VDE IEC-Ex EAC
------------------------	---

---

dielectric strength	1000 V conforming to IEC 60243-1
---------------------	----------------------------------

---

ambient air temperature for operation	-40...130 °C conforming to IEC 60216-1 -40...130 °C conforming to VDE 0304-T21
---------------------------------------	---

---

## Offer Sustainability

---

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

---

RoHS (date code: YYWW)	Compliant - since 1052 - Schneider Electric declaration of conformity
------------------------	---

---

REACH	Reference not containing SVHC above the threshold
-------	---

---

Product end of life instructions	Need no specific recycling operations
----------------------------------	---------------------------------------

---