

## Product data sheet

### Characteristics

# A9A15322

modular buzzer iRO - 230 V 50/60Hz - 70 dB



### Main

Range of product	Acti 9
Product name	Acti 9 iRO
Product or component type	Buzzer
Device short name	IRO

### Complementary

[Us] rated supply voltage	230 V AC at 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Product weight	64 g
Colour	White
Auxiliary connection terminal	Tunnel type terminalsrigid 4 mm <sup>2</sup> Tunnel type terminalsflexible 4 mm <sup>2</sup> Tunnel type terminalsflexible with ferrule 4 mm <sup>2</sup>
Wire stripping length	12 mm for bottom connection
Tightening torque	1.3 N.m

### Environment

Noise level	70 dB
Type of sound	Buzzer
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54 g
Package 1 Height	7 cm
Package 1 width	1.8 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12

Package 2 Weight	710 g
Package 2 Height	8 cm
Package 2 width	9.5 cm
Package 2 Length	22.5 cm
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Weight	9.032 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------