

Product data sheet

Characteristics

PDL380M32-VW

Switch 300 Series Mechanism - 250 V - 32 A / 20AX - Vivid White



Main

Range of product	PDL Iconic
Product or component type	Switch
Device application	Lighting Appliances
Device presentation	Mechanism
Provided equipment	Switch Rocker dolly
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Motor M-rating AS3133	M100
Load type	Inductive

Complementary

Switch function	1-way
Actuator	Rocker
Fixing mode	Locking bar
Surface finish	Matt
Surface treatment	Untreated
Rated current	32 A at 250 V AC 50 Hz
Electrical durability	5000 cycles conforming to AS/NZS 60669
Connections - terminals	2 screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	2.5 mm ² for stranded cable(s)
Wire stripping length	10 mm
Material	PC (polycarbonate): housing PA66: housing PC (polycarbonate): dolly ABS (acrylonitrile butadiene-styrene): dolly
Height	23 mm
Width	23 mm
Depth	32 mm
Product weight	0.016 kg

Environment

Dielectric strength	5000 V
Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Product certifications	RCM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	31 g
Package 1 Height	23 mm
Package 1 width	28 mm
Package 1 Length	31 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile