

Product data sheet

Characteristics

PDL395H4-VW

PDL Iconic, switched socket, 4 switch & 4 socket, horiz, 10 A, Vivid White



Main

| | |
|----------------------------|---------------------|
| Range | PDL Iconic |
| Product or component type | Switched socket |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutter |

Complementary

| | |
|--------------------------------|--|
| Device mounting | Flush |
| Number of power socket outlets | 4 |
| Number of rocker | 4 |
| Range compatibility | socket-outlet |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Fixing mode | By screw |
| Installation direction | Horizontal |
| Colour | Vivid white (VW) |
| Surface finish | Matt |
| Type of packing | Polybag |
| Quantity per set | Set of 1 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A at 250 V AC 50 Hz |
| Electrical durability | 12000 cycles |
| Connections - terminals | 3 screw terminals |
| Screwdriver shape | Square drive no 1 (SQ1) Philips No 2 |
| Clamping connection capacity | 1 x 2.5...4 x 2.5 mm ² for rigid cable(s) 1 x 2.5...4 x 2.5 mm ² for stranded cable(s) 1 x 2.5...4 x 2.5 mm ² for flexible cable(s) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate): fixing frame PP (polypropylene): flaps POM (polyoxymethylene): shutter PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin POM (polyoxymethylene): locking bar |
| Height | 78 mm |
| Width | 216 mm |
| Depth | 27 mm |
| Embedding depth | 18 mm |
| Product weight | 0.216 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Standards | AS/NZS 3112 |
| Product certifications | RCM |

Packing Units

| | |
|------------------|------------|
| Package 1 Weight | 1.000 g |
| Package 1 Height | 43.000 mm |
| Package 1 width | 78.000 mm |
| Package 1 Length | 172.000 mm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |