

Product data sheet

Characteristics

PDLP361-BK

Pro Series, switch, architrave, vertical, 1 or 2 way, 10 AX, Black



Main

| | |
|---------------------------|------------|
| Range | Pro Series |
| Product or component type | Switch |
| Colour tint | Black |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |

Complementary

| | |
|--------------------------------|--|
| Device presentation | Complete product |
| Control type | Rocker |
| Device mounting | Wall |
| Installation direction | Vertical |
| Switch function | 1-pole 1/2-way |
| Number of rocker | 1 |
| Rated current | 20 A/16 AX |
| [Ue] rated operational voltage | 250 V |
| Material | PC (polycarbonate) PP (polypropylene) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene) |
| Fixing mode | By screws |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Connections - terminals | Screw terminal |
| Clamping connection capacity | 1 x 1.5...4 x 1.5 mm ² for rigid or stranded cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s) |
| Height | 113 mm |
| Width | 38 mm |
| Depth | 40 mm |
| Net weight | 0.048 kg |

Environment

| | |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Product certifications | RCM |