

Product data sheet

Characteristics

SAE_UE_MS_CSAWE

Single-Load 360° PIR Occupancy Sensor



Main

Range	ARGUS
Product or component type	Occupancy sensor
Load type	Halogen lamp <= 1000 VA Energy saving lamp <= 80 VA Incandescent lamp <= 2000 W Low voltage halogen lamp <= 1000 VA Fluorescent lamp 100 µF <= 900 VA

Complementary

Rated voltage	230 V +/- 10 % AC 50/60 Hz
Detection angle	360°
Presence detection area	PIR: 360°, 7 x 7 m
Device mounting	Flush Surface
Mounting support	Ceiling
Mounting height	2...3 m
Diameter	111 mm
Depth	66 mm

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 flush mounting IP44 surface mounting
Ambient air temperature for operation	0...45 °C indoor -20...45 °C outdoor
Standards	EN 60669-1 EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	281.82 g
Package 1 Height	7.5 cm
Package 1 width	12 cm
Package 1 Length	12 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	44
Package 2 Weight	12000 g
Package 2 Height	41 cm
Package 2 width	32.5 cm
Package 2 Length	52 cm
Unit Type of Package 3	P12

Number of Units in Package 3	440
Package 3 Weight	140000 g
Package 3 Height	950 mm
Package 3 width	800 mm
Package 3 Length	1200 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------