



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

CATALOGUE#	DESCRIPTION	BARCODE #
681M16HFS Old #: 581M16HFS	SENSOR PRINTED White Black	9416175128783 9416175159152
681M16HF Old #: 581M16HF	BLANK UNPRINTED White Black Clear	9416175117121 9416175119033 9416175124648
681M16FAL Old #: 581M16HFAL	ALARM PRINTED White	941617514711
681M16HFF Old #: 581M16HFF	FRIDGE PRINTED White	9416175158179
681M16HMW Old #: 581M16HMW	MICROWAVE PRINTED White	9416175158247

DESCRIPTION Dedicated hinged flap Switch Modules.



BOX QUANTITY 20

OUTER QUANTITY Nil

FEATURES

Hinged flap to protect the switch in either the on or off position
- prevent accidental activation

Rating: 230V - 240V a.c., 50Hz

16A Resistive

8AX Fluorescent

16AX Inductive

2 Way

Terminals accommodate 4 x 1.5mm cables each or 2 x 2.5mm cables each

Front loading module can't be knocked into wall

White module also available with clear lid - status of switch can



P D L

NEW PRODUCT DATA AND APPLICATION SHEET

be easily seen or supplied card can be utilised to label switch
inside clear lid

Lid [excluding clear lid] pre-printed

APPLICATIONS

As part of the modern kitchens where an accessible isolation switch is required but the status of the switch is in need of protection – the hinged lid and the identification of the switch function both assist in preventing accidental isolation of the appliance

Clear Lid: Where the status of a switch is in need of protection - such as where sensor lights are used or in hospitals and rest-homes
Clear lid version can be used to identify switches in addition to the protection offered.

COMMENTS

Incorporates all the features of the standard 681M16 module. Ideal for use in conjunction with the cat 693/2 double socket, which has separate bases to allow for remote and separate isolation of two appliances.