



Main

| | |
|---------------|---------|
| Colour | Grey |
| Product brand | Clipsal |

Complementary

| | |
|--------------------------------|-------------------------------|
| Colour code | GY |
| Control type | ON/OFF button Sliding type |
| Number of gangs | 1 gang |
| Pin number | 3 |
| Number of power socket outlets | 1 |
| Mounting position | Horizontal |
| Fixing mode | By screws |
| Local signalling | Without light indicator |
| Material | Plastic |
| [Ue] rated operational voltage | 250 V AC |
| [In] rated current | 10 A |
| Depth | 87 mm |
| Length | 75 mm |
| Width | 78 mm |
| Fixing center | 84 mm |

Environment

| | |
|-------------------------|-----------------------------------|
| IP degree of protection | IP54 |
| standards | AS/NZS 3112 - approval number S/1 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1301 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.