



Main

|                           |                      |
|---------------------------|----------------------|
| Range of product          | Harmony XAC          |
| Product or component type | Head for push-button |
| Component name            | XACA                 |

Complementary

|                                       |                                                                  |
|---------------------------------------|------------------------------------------------------------------|
| Marking                               | Unmarked                                                         |
| Operator additional information       | Booted                                                           |
| Cap/operator or lens colour           | Green                                                            |
| Product compatibility                 | XACA..                                                           |
| Mounting location                     | Front of enclosure                                               |
| Sale per indivisible quantity         | 10                                                               |
| Standards                             | EN/IEC 60204-32<br>EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14 |
| Ambient air temperature for operation | -25...70 °C                                                      |
| Ambient air temperature for storage   | -40...70 °C                                                      |
| Vibration resistance                  | 15 gn 10...500 Hz IEC 60068-2-6                                  |
| Shock resistance                      | 100 gn IEC 60068-2-27                                            |
| Overvoltage category                  | Class II IEC 61140                                               |
| IP degree of protection               | IP65 IEC 60529                                                   |
| IK degree of protection               | IK08 EN 50102                                                    |
| Product weight                        | 0.01 kg                                                          |

Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.