

LUMEN SELECT™ COLOUR SELECT™

NIPPER BATTEN



PRODUCT DETAILS


Size: 2ft/600mm, 4ft/1200mm, 5ft/1500mm
 Rated life: L80 B50 54000hrs
 LED: Colour Select 4000K/5000K/6500K, CRI80, 5SDCM
 Beam angle: Symmetrical, 120°
 Driver: Integral, Lumen Select, Non dimmable, Flicker free design
 Rating: IP20, Class I
 Operating temperature: 0°C to +40°C
 Housing: Steel
 Finishing: White RAL9003, Powder coated
 Diffuser/Lens: Polycarbonate (PC), Frosted, Insect proof
 Connection: Removable LED module with quick release clips and connector, Ø20mm knockout for conduit or cable glands, Center cable entry, End to end mounting
 Warranty*: 5 year

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Dimming, Emergency

APPLICATIONS

Surface mounted (ceiling/wall), Internal
 Commercial, Retail, Residential



VERSION	L (MM)	W (MM)	H (MM)
NIPBAT202ECS	630	130	74
NIPBAT404ECSLS	1230	130	74
NIPBAT505ECSLS	1500	130	74

CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
NIPBAT202ECS	NIPPER BATTEN 2FT 18W 4/5/65K @ 4K	18W	1900LM	106LM/W	1.20KG
NIPBAT404ECSLS	NIPPER BATTEN 4FT 20/26/31/36W 4/5/65K @ 4K	20W	2400LM	120LM/W	2.10KG
		26W	3000LM	115LM/W	
		31W	3400LM	110LM/W	
		36W	4000LM	111LM/W	
NIPBAT505ECSLS	NIPPER BATTEN 5FT 29/36/44/51W 4/5/65K @ 4K	29W	4000LM	138LM/W	2.60KG
		36W	5000LM	139LM/W	
		44W	5900LM	134LM/W	
		51W	6700LM	131LM/W	

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.