



Nexans
Ref.: XDAB22AA004AALP
Country Ref.: 8256
EAN 13: 99416079023354

CONTACT

Sales and Customer Solutions
Phone: 0800 639 267
sales.nz@nexans.com

Aluminium conductor, XLPE insulation. Made to ASNZS 3560.1.

STANDARDS

Product AS/NZS 3560.1

Application

Aerial Bundled Cable is designed for residential and rural areas for reducing the bushfire hazards. The XLPE covering contains a high level of carbon black for UV resistance. It is designed for where reliability, safety and low installation cost are required, but it is only for short spans due to increased weight.



Rated Voltage Uo/U (Um)
0.6/ 1 (1.2) kV



Maximum operating temperature
80 °C



U.V resistance
Yes

CHARACTERISTICS

Construction characteristics

Pilot wires	None
Conductor material	Aluminum
Insulation	XLPE
Sheath colour	-

Dimensional characteristics

Number of cores	4
Conductor cross-section	95 mm ²
Conductor diameter	11.4 mm
Insulation sheath thickness	1.7 mm
Nominal overall diameter	38.4 mm
Approximate weight	1.35 kg/m

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	0.6/ 1 (1.2) kV
---	-----------------

Mechanical characteristics

Minimum breaking load	53.2 kN
-----------------------	---------

Usage characteristics

Maximum operating temperature	80 °C
U.V resistance	Yes

NOTE

1. Coefficient of linear expansion $23.0 \times 10^{-6}/^{\circ}\text{C}$.
 - a. Modulus of elasticity 59 GPa up to and including 50mm² and 56 GPa for conductors above 50mm².

Current ratings are based on an ambient temperature of 30°C, a maximum conductor temperature of 80°C, wind speed of 1 m/s and intensity of solar radiation 1000 w/m².