

# >CU VintolsCU Cantols

CU VINTOL 16 NL WH V75 1HM

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** BABP15A1001WVNA

**Country Ref.:** 8131.1

Cu conductor, PVC insulated, PVC sheath. 0.6/1 kV. Made to AS/NZS 5000.1

## DESCRIPTION

### Application

- Industrial and commercial applications (predominantly)
- Some domestic applications
- For use in various situations to supply the main power from the point of supply (either single or three phase application) to buildings, equipment, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc. Commonly used in Power Authority work.



## STANDARDS

**National AS/NZS 5000.1**

# >CU VintolsCU Cantols

CU VINTOL 16 NL WH V75 1HM

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

## CHARACTERISTICS

### Construction characteristics

Sheath colour	White
Conductor material	Copper
Type of conductor	Circular, stranded
Insulation	PVC
Outer sheath	PVC
Insulation colour	White
With Green/Yellow core	No
With smaller neutral conductor	No

### Dimensional characteristics

Conductor cross-section	16 mm <sup>2</sup>
Nominal overall diameter	10.0 mm
Gland Size (A2 or A2F)	20
Approximate weight	0.23 kg/m
Neutral conductor section (when smaller)	- mm <sup>2</sup>
Number of cores	1

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Permissible short circuit current conductor 1s	1.8 kA
Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	0.6/ 1 (1.2) kV

### Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

### Usage characteristics

Max. conductor temperature in service	75 °C
Packaging	-

# >CU VintolsCU Cantols

CU VINTOL 16 NL WH V75 1HM

Contact

Sales and Customer Solutions  
sales.nz@nexans.com

## CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - SINGLE CONDUCTOR PVC

Copper conductor - Circular stranded - Insulation PVC Aluminum conductor - Circular stranded except 240 mm<sup>2</sup> Compact circular stranded - Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm <sup>2</sup> ]																				
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al						
16	56	-	46	-	47	-	71	-	109	-	98	-	41							
	Air Spaced from Surface, Unenclosed								Air touching, unenclosed								Air enclosed			
	Buried direct								Buried in single-way duct								Buried in multi-way duct			
	Cable surrounded by thermal insulation, unenclosed																			

### Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at [www.standards.co.nz](http://www.standards.co.nz).

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

## CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - SINGLE CONDUCTOR PVC

Single Conductor PVC (three phase) PVC insulation Unarmoured Sheathed or unsheathed For cables up to and including 0.6/1 kV @ 50 Hz AC.

Conductor cross-section [mm <sup>2</sup> ]																				
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al						
16	88	-	82	-	71	-	114	-	99	-	86	-	41							
	Air Spaced from Surface, Unenclosed								Air touching, unenclosed								Air enclosed			
	Buried direct								Buried in single-way duct								Buried in multi-way duct			
	Cable surrounded by thermal insulation, unenclosed																			

### Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at [www.standards.co.nz](http://www.standards.co.nz).

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 5/11/21 [www.nexans.co.nz](http://www.nexans.co.nz) Page 3 / 4

# >CU VintolsCU Cantols

CU VINTOL 16 NL WH V75 1HM

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m