

# CU Vintols

CU VINTOL 70 NL WH V75

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** BABP20AA001WVNA

**Country Ref.:** 9981

Cu conductor, PVC insulated, PVC sheath. 0.6/1 kV. Made to AS/NZS 5000.1

## DESCRIPTION

### Application

- Industrial and commercial applications (predominantly)
- Some domestic applications
- For use in various situations to supply the main power from the point of supply (either single or three phase application) to buildings, equipment, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc. Commonly used in Power Authority work.



## STANDARDS

**National AS/NZS 5000.1**

## CHARACTERISTICS

### Construction characteristics

Sheath colour	White
Conductor material	
Type of conductor	Circular, stranded
Insulation	PVC
Outer sheath	PVC
Insulation colour	White
With Green/Yellow core	No
With smaller neutral conductor	No

### Dimensional characteristics

Conductor cross-section	70 mm <sup>2</sup>
Nominal overall diameter	16.4 mm
Gland Size (A2 or A2F)	25
Approximate weight	0.82 kg/m
Neutral conductor section (when smaller)	- mm <sup>2</sup>
Number of cores	1

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	0.268 Ohm/km
Permissible short circuit current conductor 1s	7.8 kA
Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	0.6/ 1 (1.2) kV

### Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

### Usage characteristics

Max. conductor temperature in service	75 °C
Packaging	-

### CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - SINGLE CONDUCTOR PVC

Copper conductor - Circular stranded - Insulation PVC Aluminum conductor - Circular stranded except 240 mm<sup>2</sup> Compact circular stranded - Insulation PVC Max. Conductor Temperature 75C

Conductor cross-section [mm <sup>2</sup> ]																				
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Al	Cu	Al							
70	136	197	111	163	107	150	174	237	251	195	227	176	-							
	Air Spaced from Surface, Unenclosed								Air touching, unenclosed								Air enclosed			
	Buried direct								Buried in single-way duct								Buried in multi-way duct			
	Cable surrounded by thermal insulation, unenclosed																			

#### Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at [www.standards.co.nz](http://www.standards.co.nz).

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

### CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - SINGLE CONDUCTOR PVC

Single Conductor PVC (three phase) PVC insulation Unarmoured Sheathed or unsheathed For cables up to and including 0.6/1 kV @ 50 Hz AC.

Conductor cross-section [mm <sup>2</sup> ]																				
	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al	Cu	Al						
70	225	174	210	163	173	135	256	199	226	175	198	154	-							
	Air Spaced from Surface, Unenclosed								Air touching, unenclosed								Air enclosed			
	Buried direct								Buried in single-way duct								Buried in multi-way duct			
	Cable surrounded by thermal insulation, unenclosed																			

#### Note

© Copyright Standards New Zealand 2012.

Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at [www.standards.co.nz](http://www.standards.co.nz).

# CU Vintols

CU VINTOL 70 NL WH V75

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m