

CU Cantols

CU CANTOL 120

Contact

General Sales
Phone: 0508 NEXANS
sales.nz@nexans.com

Nexans ref.: BDBC23AA001CXNA

Country ref.: 2440

Cu conductor, XLPE insulated, Black PVC sheath. 0.6/1 kV. Made to AS/NZS 5000.1

DESCRIPTION

Application

- Industrial and commercial applications (predominantly)
- Some domestic applications
- For use in various situations to supply the main power from the point of supply (either single or three phase application) to buildings, equipment, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc. Commonly used in Power Authority work.



STANDARDS

National AS/NZS 5000.1

CHARACTERISTICS

Construction characteristics

| | |
|--------------------------------|-----------------------------|
| Conductor material | Copper |
| Type of conductor | Circular compacted stranded |
| Insulation | XLPE |
| Outer sheath | PVC |
| Sheath colour | Black |
| With Green/Yellow core | No |
| With smaller neutral conductor | No |

Dimensional characteristics

| | |
|--------------------------|---------------------|
| Conductor cross-section | 120 mm ² |
| Nominal overall diameter | 18.6 mm |
| Gland Size (A2 or A2F) | 25 |
| Approximate weight | 1.27 kg/m |
| Number of cores | 1 |

Electrical characteristics

| | |
|---|-----------------|
| Max. DC resistance of the conductor at 20°C | 0.153 Ohm/km |
| Permissible short circuit current conductor 1s | 17.2 kA |
| Rated Voltage U ₀ /U (U _m) | 0.6/ 1 (1.2) kV |

Mechanical characteristics

| | |
|-------------------|-------|
| Cable flexibility | Rigid |
|-------------------|-------|

Usage characteristics

| | |
|---------------------------------------|-------|
| Max. conductor temperature in service | 90 °C |
|---------------------------------------|-------|

CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper conductor - Circular compacted stranded - Insulation XLPE Aluminium conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

| Conductor cross-section [mm ²] |  |  |  |  |  |  |  |
|---|---|---|---|---|---|---|---|
| | Cu | Cu | Cu | Cu | Cu | Cu | Cu |
| 16 | 119 | 95 | 92 | 149 | 120 | 107 | 47 |
| 25 | 160 | 129 | 124 | 192 | 156 | 140 | 64 |
| 35 | 195 | 158 | 149 | 230 | 187 | 168 | 79 |
| 50 | 238 | 194 | 183 | 273 | 226 | 202 | - |
| 70 | 300 | 246 | 224 | 335 | 276 | 249 | - |
| 95 | 372 | 306 | 281 | 401 | 331 | 305 | - |
| 120 | 432 | 358 | 321 | 457 | 383 | 348 | - |
| 150 | 495 | 413 | 362 | 514 | 429 | 391 | - |
| 185 | 574 | 480 | 426 | 581 | 495 | 453 | - |
| 240 | 684 | 574 | 507 | 674 | 574 | 532 | - |
| 300 | 790 | 666 | - | 761 | 663 | 601 | - |
| 400 | 920 | 779 | - | 865 | 755 | 699 | - |
| 500 | 1063 | 903 | - | 977 | 856 | 791 | - |
| 630 | 1224 | 1045 | - | 1098 | 995 | 916 | - |

| | | |
|--|---|--|
|  Air Spaced from Surface, Unenclosed |  Air touching, unenclosed |  Air enclosed |
|  Buried direct |  Buried in single-way duct |  Buried in multi-way duct |
|  Cable surrounded by thermal insulation, unenclosed | | |

Note © Copyright Standards New Zealand 2012. Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m

CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - SINGLE CONDUCTOR XLPE

Copper conductor - Circular compacted stranded - Insulation XLPE Aluminum conductor - Circular compacted stranded - Insulation XLPE Max. Conductor Temperature 90C

| Conductor cross-section [mm ²] |  |  |  |  |  |  |  |
|---|---|---|---|---|---|---|---|
| | Cu | Cu | Cu | Cu | Cu | Cu | Cu |
| 16 | 101 | 95 | 79 | 125 | 108 | 92 | 47 |
| 25 | 138 | 129 | 107 | 162 | 141 | 121 | 64 |
| 35 | 169 | 158 | 132 | 193 | 169 | 147 | 79 |
| 50 | 207 | 194 | 157 | 229 | 203 | 174 | - |
| 70 | 264 | 246 | 201 | 280 | 248 | 217 | - |
| 95 | 328 | 306 | 242 | 335 | 295 | 261 | - |
| 120 | 384 | 358 | 287 | 381 | 342 | 304 | - |
| 150 | 443 | 413 | 325 | 428 | 383 | 342 | - |
| 185 | 515 | 479 | 369 | 484 | 442 | 388 | - |
| 240 | 616 | 573 | 439 | 560 | 510 | 456 | - |
| 300 | 713 | 662 | 516 | 630 | 591 | 525 | - |
| 400 | 832 | 772 | 587 | 715 | 670 | 596 | - |
| 500 | 961 | 893 | 696 | 805 | 756 | 693 | - |
| 630 | 1111 | 1032 | 785 | 902 | 877 | 778 | - |
| 800 | - | - | - | - | - | - | - |

| | | |
|--|---|--|
|  Air Spaced from Surface, Unenclosed |  Air touching, unenclosed |  Air enclosed |
|  Buried direct |  Buried in single-way duct |  Buried in multi-way duct |
|  Cable surrounded by thermal insulation, unenclosed | | |

Note © Copyright Standards New Zealand 2012. Content in this table and the typical New Zealand installation conditions are derived from AS/NZS 3008.1.2:2010 and has been reproduced or adapted with permission from Standards New Zealand under Copyright Licence 000926. Please refer to the complete Standard for full details available for purchase from Standards New Zealand at www.standards.co.nz. The values are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m