

# Cempex Cables

CU CEMPEX 4X 16+6E

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** HTHP15AA004CXEM

**Country Ref.:** 7656

Cu Conductors, XLPE insulation, Laid up, Black PVC sheath, 0.6/1 kV. Made to AS/NZS 5000.1. Circular multicore with integral earth.

## DESCRIPTION

### Application

- Industrial, commercial and domestic applications.
- For use in various situations to supply the main power from the point of supply to buildings, equipment, sheds, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc.



## STANDARDS

**National AS/NZS 5000.1**

### CHARACTERISTICS

#### Construction characteristics

Type of conductor	Circular compacted stranded
Conductor material	Copper
Insulation	XLPE
Outer sheath	PVC
Conductor flexibility	Class 2
Conductor shape	Circular
Core identification	Red, White, Blue, Black, Green/Yellow
Sheath colour	Black
With Green/Yellow core	Yes
With smaller neutral conductor	No

#### Dimensional characteristics

Number of cores	5
Conductor cross-section	16 mm <sup>2</sup>
Earth conductor cross section	6 mm <sup>2</sup>
Nominal overall diameter	21.5 mm
Gland Size (A2 or A2F)	32
Approximate weight	0.9 kg/m
Neutral conductor section (when smaller)	- mm <sup>2</sup>

#### Electrical characteristics

Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Permissible short circuit current conductor 1s	- kA
Rated Voltage U <sub>o</sub> /U (U <sub>m</sub> )	0.6/ 1 (1.2) kV

#### Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

#### Usage characteristics

Max. conductor temperature in service	90 °C
---------------------------------------	-------

### CURRENT CARRYING CAPACITIES THREE PHASE (IN AMPS) - 3 -4 CORE PLUS EARTH CU CEMPEX CABLES

Copper Conductor Circular stranded Insulation XLPE Max. Conductor Temperature 90C

Conductor cross-section [mm <sup>2</sup> ]	 Cu	 Cu	 Cu	 Cu	 Cu	 Cu
16	97	91	75	118	87	45
						
						

#### Note

Content from AS/NZS 3008.1.2:2010 has been reproduced with the permission from Standards New Zealand under Copyright Licence 000926. Please see the Standard for full details.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 10/01/22 www.nexans.co.nz Page 2 / 3

# Cempex Cables

CU CEMPEX 4X 16+6E

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

The values in this table are for typical New Zealand installation conditions of:

- Ambient Air Temperature: 30°C
- Soil Temperature: 15°C
- Soil Thermal Resistivity: 1.2 K.m/W
- Depth of Burial: 0.5 m