

# Al Aerial Bundled cables (ABC)

AL AERIAL ABC: LV 2X 35^

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** XDAB18AA002AALL

**Country Ref.:** 1566

Aluminium conductor, XLPE insulation. Made to ASNZS 3560.1.

## DESCRIPTION

### Application

Aerial Bundled Cable is designed for residential and rural areas for reducing the bushfire hazards. The XLPE covering contains a high level of carbon black for UV resistance. It is designed for where reliability, safety and low installation cost are required, but it is only for short spans due to increased weight.



## STANDARDS

**National AS/NZS 3560.1**

# Al Aerial Bundled cables (ABC)

AL AERIAL ABC: LV 2X 35^

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

## CHARACTERISTICS

### Construction characteristics

Pilot wires	None
Conductor material	Aluminum
Insulation	XLPE
Sheath colour	-

### Dimensional characteristics

Number of cores	2
Conductor cross-section	35 mm <sup>2</sup>
Conductor diameter	6.9 mm
Insulation sheath thickness	1.3 mm
Nominal overall diameter	20.6 mm
Approximate weight	0.26 kg/m

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	0.6/ 1 (1.2) kV
---	-----------------

### Mechanical characteristics

Minimum breaking load	9.8 kN
-----------------------	--------

### Usage characteristics

Maximum operating temperature	80 °C
-------------------------------	-------

## NOTE

1. Coefficient of linear expansion  $23.0 \times 10^{-6}/^{\circ}\text{C}$ .
  - a. Modulus of elasticity 59 GPa up to and including 50mm<sup>2</sup> and 56 GPa for conductors above 50mm<sup>2</sup>.

Current ratings are based on an ambient temperature of 30°C, a maximum conductor temperature of 80°C, wind speed of 1 m/s and intensity of solar radiation 1000 w/m<sup>2</sup>.