



V SERIES RANGE

V12 / V SERIES DISTRIBUTION BOARD

FEATURES

- Extra depth behind DIN Rail for cable space
- Latching doors
- Easily removable DIN Rails via keyhole

Cover Assembly Size (H x W)

250 x 275mm

Base Dimensions (H x W x D)

220 x 250 x 65mm

V12

Input Voltage	400V AC
Max Current Rating	63A
DIN Capacity	12 Ways
Number of DIN Rail Rows	1 Row
Earth Bar	1 x 10 Way
Neutral Bar	1 x 3 Way Linked 2 x 3 Way
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x 12 Way Insulated Phase Bar 2 x 3 Way Pole Filler 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V20 / V SERIES DISTRIBUTION BOARD

FEATURES

- Extra depth behind DIN Rail for cable space
- Latching doors
- Easily removable DIN Rails via keyhole

Cover Assembly Size (H x W)

250 x 419mm

Base Dimensions (H x W x D)

220 x 395 x 66mm

V20

Input Voltage	400V AC
Max Current Rating	100A
DIN Capacity	20 Ways
Number of DIN Rail Rows	1 Row
Earth Bar	1 x 14 Way
Neutral Bar	1 x 4 Way Linked 4 x 3 Way
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x 20 Way Insulated Phase Bar 2 x 3 Way Pole Filler 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V30 / V SERIES DISTRIBUTION BOARD

FEATURES

- Extra depth behind DIN Rail for cable space
- Latching doors
- Easily removable DIN Rails via keyhole

Cover Assembly Size (H x W)

400 x 335mm

Base Dimensions (H x W x D)

375 x 305 x 66mm

V30

Input Voltage	400V AC
Max Current Rating	100A
DIN Capacity	30 Ways
Number of DIN Rail Rows	2 Row
Earth Bar	1 x 24 Way
Neutral Bar	1 x 8 Way Linked 6 x 3 Way
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	2 x 15 Way Insulated Phase Bar 4 x 3 Way Pole Filler 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V40 / V SERIES DISTRIBUTION BOARD

FEATURES

- Extra depth behind DIN Rail for cable space
- Latching doors
- Easily removable DIN Rails via keyhole
- Matching data board and indoor meter board for uniform look

Cover Assembly Size (H x W)

435 x 420mm

Base Dimensions (H x W x D)

412 x 395 x 66mm

V40

Input Voltage	400V AC
Max Current Rating	100A
DIN Capacity	40 Ways
Number of DIN Rail Rows	2 Row
Earth Bar	1 x 30 Way
Neutral Bar	1 x 8 Way Linked 8 x 3 Way
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	2 x 20 Way Insulated Phase Bar 4 x 3 Way Pole Filler 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V60 / V SERIES DISTRIBUTION BOARD

FEATURES

- Extra depth behind DIN Rail for cable space
- Latching doors
- Easily removable DIN Rails via keyhole

Cover Assembly Size (H x W)

685 x 420mm

Base Dimensions (H x W x D)

650 x 390 x 65mm

V60

IP Rating IP40

Input Voltage 400V AC

Max Current Rating 100A

DIN Capacity 60 Ways

Number of DIN Rail Rows 3 Rows

Earth Bar 2 x 30 Way

Neutral Bar 1 x 30 Way Linked
9 x 3 Way

Mounting Flush

Base Box Material Galvanised Steel

Door & Surround Material Polycarbonate

Door & Surround Colour Appliance White

Supplied With
3 x 20 Way Insulated Phase Bar
4 x 6 Way Pole Filler
1 x Circuit Label Chart
2 x Copper Link
1 x Earth Wire 650 x 6mm²
1 x Earth Wire 200 x 6mm²

Warranty 1 Year



V SERIES RANGE

V40CMBM / V SERIES COMBINED METER BOARD

FEATURES

- Metal base
- Matches V Series switchboard aesthetic
- Latching doors

Box Dimensions (H x W x D)

414 x 396 x 92mm

Surround Dimensions (H x W)

435 x 420mm

Meter Tray to Cover Depth

74mm

V40CMBM

Input Voltage	400V AC
DIN Capacity	20 Ways
Number of DIN Rail Rows	1 Row
Earth Bar	1 x 14 Way
Neutral Bar	1 x 8 Way Linked 3 x 3 Way
Mounting	Flush
Base Box Material	Galvanised Steel
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x 20 Way Insulated Phase Bar 1 x 6 Way Pole Filler 1 x Circuit Label Chart 1 x Internal Clear Cover 6 x Grommet 45mm 8 x Grommet Blank 45mm 8 x Self Tapping Screw 12.7mm 4 x Spire Nut No.8
Warranty	1 Year



V SERIES RANGE

V40MB / V SERIES METER BOARD

FEATURES

- Internal use only
- Plastic doors
- Matches V Series switchboard aesthetic

Box Dimensions (H x W x D)

412 x 395 x 66mm

Cover Assembly Size (H x W)

435 x 420mm

Meter Tray to Cover Depth

74mm

V40MB

Input Voltage	400V AC
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x Internal Clear Cover
Warranty	1 Year



V SERIES RANGE

V40MB1 / V SERIES METER BOARD

FEATURES

- Internal use only
- Plastic doors
- Matches V Series switchboard aesthetic

Box Dimensions (H x W x D)

412 x 395 x 66mm

Cover Assembly Size (H x W)

435 x 420mm

Meter Tray to Cover Depth

74mm

V40MB1

Input Voltage	400V AC
Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x Internal Clear Cover 1 x Din Rail 4 Way 1 x 3 Way Pole Filler 1 x Insulated Neutral Stud 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V40T / V SERIES METER BOARD

FEATURES

- Matches V Series switchboard aesthetic
- Twin covers for separate meter and distribution

Box Dimensions (H x W x D)

850 x 400 x 80mm

Surround Dimensions (H x W)

875 x 420mm

Meter Tray to Cover Depth

80mm

V40T

Input Voltage	400V AC
Max Current Rating	100A
DIN Capacity	40 Ways
Number of DIN Rail Rows	2 Rows
Earth Bar	1 x 28 Way
Neutral Bar	1 x 8 Way Linked 6 x 3 Way
Mounting	Flush
Base Box Material	Galvanised Steel
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	1 x Internal Clear Cover 2 x 20 Way Insulated Phase Bar 4 x 3 Way Pole Filler 1 x Circuit Label Chart
Warranty	1 Year



V SERIES RANGE

V40T135 / V SERIES METER BOARD

FEATURES

- Supplied with Depth Extension Spacer
- Matches V Series switchboard aesthetic
- Twin covers for separate meter and distribution

Box Dimensions (H x W x D)

850 x 400 x 80mm

Surround Dimensions (H x W)

875 x 420mm

Depth Extension Spacer Dimensions (H x W x D)

881 x 431 x 50mm

Meter Tray to Cover Depth

125mm

V40T135

Input Voltage 400V AC

Max Current Rating 100A

DIN Capacity 40 Ways

Number of DIN Rail Rows 2 Rows

Earth Bar 1 x 28 Way

Neutral Bar 1 x 8 Way Linked
6 x 3 Way

Mounting Flush

Base Box Material Galvanised Steel

Door & Surround Material Polycarbonate

Door & Surround Colour Appliance White

Supplied With
1 x Internal Clear Cover
2 x 20 Way Insulated
Phase Bar
4 x 3 Way Pole Filler
1 x Circuit Label Chart

Warranty 1 Year



V SERIES RANGE

VCC40B / V SERIES COMMUNICATION BOARD

FEATURES

- Matches V Series switchboard aesthetic
- Comes complete with universal gear tray and 230V AC socket outlets
- Easy break-away knock outs for cable installs
- Compact size suitable for small to medium installs
- Plastic construction reduces likelihood of wifi interference

Box Dimensions (H x W x D)

412 x 395 x 66mm

Surround Dimensions (H x W)

435 x 420mm

VCC40B

Mounting	Flush
Base Box Material	Polycarbonate
Door & Surround Material	Polycarbonate
Door & Surround Colour	Appliance White
Supplied With	2 x 10A Sockets 1 x Circuit Label Chart
Warranty	1 Year