

WILLIS LED FLOODLIGHTS







FEATURES

- Toolless adjustment
- Bracket designed to be easily fixed to a structure without having to remove the light
- Slim Profile
- Includes 0.5m flex
- 3 Year Warranty

WILLIS LED FLOODLIGHTS	
IP Rating	IP66
UGR	<22
Colour Temperature	5000K
CRI	75+
Construction Material	Aluminium / Glass / Steel
Operating Temperature	-25°C to 45°C
Input Voltage	230V AC
Beam Angle	120°
LED Lifetime	60,000hrs

WILLIS LED FLOODLIGHTS







CODE	WILLIS10	WILLIS30	WILLIS50	WILLIS100	WILLIS150	WILLIS200
Efficacy	100lm/W	100lm/W	120lm/W	120lm/W	120lm/W	120lm/W
Lumen Output	1000lm	3000lm	6000lm	12,000lm	18,000lm	24,000lm
Power	10W	30W	50W	100W	150W	200W
FITTING DIMENSIONS						
Height	115mm	115mm	200mm	250mm	312mm	448mm
Width	186mm	186mm	211mm	260mm	309mm	386mm
Depth	21mm	21mm	30mm	30mm	35mm	37mm



WILLIS10

WILLIS30

WILLIS50



WILLIS100

WILLIS150

WILLIS200