


## 1/2" Drive 6 Point Metric Deep Sockets

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Wrench End	Dim. C: Overall Length	⚖️	G.W.
13401	10 mm	22 mm	15.3 mm	77 mm	6	7.5 kg
13402	11 mm	22 mm	16.5 mm	77 mm	6	8.2 kg
13403	12 mm	22 mm	17.8 mm	77 mm	6	8.9 kg
13404	13 mm	22 mm	19 mm	77 mm	6	8.6 kg
13405	14 mm	22 mm	20.3 mm	77 mm	6	8.9 kg
13406	15 mm	22 mm	21.4 mm	77 mm	6	8.9 kg
13407	16 mm	22 mm	22 mm	77 mm	6	8.9 kg
13408	17 mm	22 mm	23.8 mm	77 mm	6	10.5 kg
13409	18 mm	24.8 mm	24.8 mm	77 mm	6	12.4 kg
13410	19 mm	25.9 mm	25.9 mm	77 mm	6	12.4 kg
13411	20 mm	27.8 mm	27.8 mm	77 mm	4	10.1 kg
13412	21 mm	27.8 mm	27.8 mm	77 mm	4	10.1 kg
13413	22 mm	28.3 mm	28.3 mm	77 mm	4	11.3 kg
13414	24 mm	31.8 mm	31.8 mm	77 mm	4	12.2 kg
13415	27 mm	35.8 mm	35.8 mm	77 mm	4	17 kg
13416	30 mm	39.8 mm	39.8 mm	77 mm	2	24 kg
13417	32 mm	41.8 mm	41.8 mm	77 mm	2	10.3 kg



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology-Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

**⚠️ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.**



ANISBOSMA  
DIM 3124


## 1/2" Drive 12 Point SAE Standard Length Sockets

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Wrench End	Dim. C: Overall Length	⚖️	G.W.
13501	5/16 in	22.2 mm	12.5 mm	37.8 mm	6	4.9 kg
13502	3/8 in	22.2 mm	14.5 mm	37.8 mm	6	4.9 kg
13503	7/16 in	22.2 mm	17 mm	37.8 mm	6	5.2 kg
13504	1/2 in	22.2 mm	18.8 mm	37.8 mm	6	5.2 kg
13505	9/16 in	22.2 mm	20.6 mm	37.8 mm	6	5.4 kg
13506	5/8 in	22.2 mm	22.2 mm	37.8 mm	6	5.7 kg
13507	11/16 in	23.8 mm	23.8 mm	37.8 mm	6	5.8 kg
13508	3/4 in	25.9 mm	25.9 mm	37.8 mm	6	6.1 kg
13509	13/16 in	27.9 mm	27.9 mm	37.8 mm	4	4.8 kg
13510	7/8 in	29.9 mm	29.9 mm	37.8 mm	4	5.9 kg
13511	15/16 in	31.9 mm	31.9 mm	37.8 mm	4	6.5 kg
13512	1 in	33.9 mm	33.9 mm	40 mm	4	8.7 kg
13513	1-1/16 in	35.9 mm	35.9 mm	42 mm	4	8.7 kg
13514	1-1/8 in	37.9 mm	37.9 mm	42 mm	4	9.9 kg
13515	1-1/4 in	41.9 mm	41.9 mm	42 mm	2	6.1 kg



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology-Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

**⚠️ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.**



ANISBOSMA  
DIM 3121


## 1/2" Drive 12 Point Metric Standard Length Sockets

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Wrench End	Dim. C: Overall Length	⚖️	G.W.
13619	8 mm	22.2 mm	15.3 mm	38 mm	6	84
13620	9 mm	22.2 mm	14.3 mm	38 mm	6	84
13621	10 mm	22.2 mm	15.3 mm	38 mm	6	84
13622	11 mm	22.2 mm	16.5 mm	38 mm	6	84
13623	12 mm	22.2 mm	17.8 mm	38 mm	6	84
13624	13 mm	22.2 mm	19 mm	38 mm	6	84
13625	14 mm	22.2 mm	20.3 mm	38 mm	6	84
13626	15 mm	22.2 mm	21.4 mm	38 mm	6	84
13627	16 mm	22.2 mm	22.2 mm	38 mm	6	84
13628	17 mm	23.9 mm	23.9 mm	38 mm	6	72
13629	18 mm	24.9 mm	24.9 mm	38 mm	6	72
13630	19 mm	25.9 mm	25.9 mm	38 mm	6	72
13631	20 mm	27.8 mm	27.8 mm	38 mm	4	48
13632	21 mm	27.9 mm	27.9 mm	38 mm	4	48
13633	22 mm	28.9 mm	28.9 mm	38 mm	4	48
13634	23 mm	31.9 mm	31.9 mm	38 mm	4	48
13635	24 mm	31.9 mm	31.9 mm	38 mm	4	48
13636	27 mm	35.9 mm	35.9 mm	40 mm	4	48
13637	30 mm	39.9 mm	39.9 mm	42 mm	2	24
13638	32 mm	41.9 mm	41.9 mm	42 mm	2	24



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology-Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

**⚠️ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.**



ANISBOSMA  
DIM 3124


## 1/2" Drive 12 Point Metric Deep Sockets

Cat. No.	Fastener Size	Dim. A: Drive End	Dim. B: Wrench End	Dim. C: Overall Length	⚖️	G.W.
13810	10 mm	22 mm	15.3 mm	77 mm	6	84
13811	12 mm	22 mm	17.8 mm	77 mm	6	84
13812	13 mm	22 mm	19 mm	77 mm	6	84
13813	14 mm	22 mm	20.3 mm	77 mm	6	84
13814	16 mm	22 mm	22 mm	77 mm	6	84
13817	17 mm	23.8 mm	23.8 mm	77 mm	6	84
13818	18 mm	24.8 mm	24.8 mm	77 mm	6	84
13819	19 mm	25.8 mm	25.8 mm	77 mm	6	84



- Made of Chrome Vanadium steel
- Double Line (SAE) & Knurled Line (MM) to easily identify Standard vs. Metric Sockets
- Surface Drive® Technology-Radius corner design provides 15%-20% more torque, extends fastener life and reduces slippage
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Specifically heat treated for the correct balance of strength and durability

**⚠️ These sockets should never be used on power drivers, pneumatic impact wrench and/or extenders.**



ANISBOSMA  
DIM 3124