

## 24V POWER SUPPLIES | BOKE 20W, 30W, 60W | IP20



CODE	OUTPUT WATTS	OUTPUT AMPS	POWER FACTOR	AC INRUSH CURRENT	DIMENSIONS
BK-PGV020-24V0	20W	0.83A	0.90	11.4A peak, 232us duration (50% Ipeak)	W50 × H13.5 × L129mm
BK-PGV030-24V0	30W	1.25A	0.95	12.75A peak, 290us duration (50% Ipeak)	W50 × H16 × L155mm
BK-PGV060-24V0	60W	2.5A	0.95	19.2A peak, 360us duration (50% Ipeak)	W57.5 × H18 × L160mm

INPUT VOLTS	200–240V AC	WARRANTY	5 years	INGRESS PROTECTION	Indoor use only
OPERATING TEMP.	-25°C ~ +45°C	COMPLIANCE		HOUSING	Plastic
DISTANCE FROM INSTALLATION (Secondary Output)	Recommended under 10 metres			MOUNTING	Mounting tabs at each end
				ELECTRICAL PROTECTION	Short circuit, overload protection
				CONNECTION METHOD	<b>20W:</b> Concealed push terminals Input cable: 0.75–1mm TPS <b>30W/60W:</b> Concealed screw terminals Input cable: 0.5-2.5mm TPS
				CONTROL	Dimmable on the secondary output only by PWM